

Glossary

action procedure A procedure that performs an action in response to the user holding the mouse button down while the cursor is in a control.

activate event A type of event that indicates that a window is becoming active or inactive. Each activate event specifies the window to be changed and the direction of the change (that is, whether it's becoming active or becoming inactive).

active control A control in which the Control Manager responds to a user's mouse actions by providing visual feedback.

active window The frontmost window on the desktop, the one in which the user is currently working. The active window is designated by racing stripes in the title bar, active controls, and highlighted selections.

A5 world An area of memory in an application's partition that contains the QuickDraw global variables, the application global variables, the application parameters, and the jump table—all of which are accessed through the A5 register.

alert An alert sound, an alert box, or both. Alerts warn the user of an unusual or a potentially undesirable situation occurring within an application. See also **alert box** and **alert sound**.

alert box A window that an application displays on the screen to warn the user or to report an error to the user. An alert box typically consists of text describing the situation and buttons that require the user to acknowledge or rectify the problem. An alert box may or may not be accompanied by an alert sound. See also **caution alert**, **note alert**, and **stop alert**.

alert color table resource A resource (of type 'actb') that lets an application display an alert box using colors other than the system's default window colors.

alert resource A resource (of type 'ALRT') that specifies alert sounds, a display rectangle, and an item list for an alert box.

alert sound An audible signal from the Macintosh speaker that warns the user of an unusual or a potentially undesirable situation occurring within an application. An alert sound may or may not be accompanied by an alert box.

alias An object that represents another file, directory, or volume.

alias file A file that contains a record that points to another file, directory, or volume. An alias file is displayed by the Finder as an alias.

alias record A data structure created by the Alias Manager to identify a file, directory, or volume.

alias target The file, directory, or volume described by the alias record.

Apple event A high-level event whose structure and interpretation are determined by the Apple Event Interprocess Messaging Protocol.

Apple Menu Items folder A directory located in the System Folder for storing desk accessories, applications, folders, and aliases that the user wants to display in and access from the Apple menu.

application heap An area of memory in the application heap zone in which memory is dynamically allocated and released on demand. The heap contains the application's 'CODE' segment 1, data structures, resource map, and other code segments as needed.

application partition A partition of memory reserved for use by an application. The application partition consists of free space, the application heap, the application's stack, and the application's A5 world.

GLOSSARY

auto-key event An event indicating that a key is still down after a certain amount of time has elapsed.

auxiliary window record A data structure that the Window Manager uses to tie together a list of windows and their corresponding window color information tables.

background process A process that isn't currently interacting with the user. Compare **foreground process**.

bundle bit A flag in a file's Finder information record that informs the Finder that a bundle ('BNDL') resource exists for the file. A file's Finder information record is stored in a volume's catalog file. The Finder uses the information in the bundle resource to associate icons with the file.

button A control that appears on the screen as a rounded rectangle with a title centered inside. When the user clicks a button, the application performs the action described by the button's title. Button actions are usually performed instantaneously. Examples include completing operations defined by a dialog box and acknowledging an error message in an alert box.

catalog file A special file, located on a volume, that contains information about the hierarchical organization of files and folders on that volume.

caution alert An alert box that warns the user of an operation that may have undesirable results if it's allowed to continue. A caution alert gives the user the choice of continuing the action (by clicking the OK button) or stopping the action (by clicking the Cancel button). A caution alert is identified by an icon bearing an exclamation point in the upper-left corner of the alert box. See also **note alert** and **stop alert**.

character code A value that represents a particular character. The character code that is generated depends on the virtual key code and the state of the modifier keys. In the Roman script system, character codes are specified in the extended version of ASCII (the American Standard Code for Information Interchange).

checkbox A control that appears onscreen as a small square with an accompanying title. A checkbox displays one of two settings: on

(indicated by an X inside the box) or off. When the user clicks a checkbox, the application reverses its setting. See also **radio button**.

close box The small white box on the left side of the title bar of an active window. Clicking it closes the window.

close region The area occupied by a window's close box. See also **close box**.

Command-key equivalent Refers specifically to a keyboard equivalent that the user invokes by holding down the Command key and pressing another key (other than a modifier key) at the same time.

content region The part of a window in which the contents of a document, the size box, and the window controls (including the scroll bars) are displayed.

context The information about a process maintained by the Process Manager. This information includes the current state of the process, the address and size of its partition, its type, its creator, a copy of its low-memory global variables, information about its 'SIZE' resource, and a process serial number.

control An onscreen object that the user can manipulate with the mouse. By manipulating a control, the user can take an immediate action or change a setting to modify a future action.

control color table In an item color table resource, a specification for the colors used to draw the various parts of a control.

control definition function A function that defines the appearance and behavior of a control. A control definition function, for example, draws the control. See also **standard control definition functions**.

control definition ID A number passed to control-creation routines to indicate the type of control. It consists of the control definition function's resource ID and a variation code.

control list A series of entries pointing to the descriptions of the controls associated with the window.

GLOSSARY

Control Manager A collection of routines that applications use to create and manipulate controls, especially those in windows.

Control Panels folder A directory located in the System Folder for storing control panels, which allow users to modify the work environment of their Macintosh computer.

control record A data structure of type `ControlRecord`, which the Control Manager uses to store all the information it needs for its operations on a control.

current menu list A data structure that contains handles to the menu records of all menus in the current menu bar and the menu records of any submenus or pop-up menus that an application inserts into the list.

current process The process that is currently executing and whose A5 world is valid; this process can be in the background or the foreground.

cursor Any 256-bit image, defined by a 16-by-16 bit square. The mouse driver displays the current cursor and maps the movement of the mouse to relative locations on the screen as the user moves the mouse.

custom alert box An alert box whose upper-left corner contains blank space or displays an icon other than those used by caution alerts, stop alerts, or note alerts.

customized icon An icon created by the user or by an application and stored with a resource ID of -16455 in the resource fork of a file. A file with a customized icon has the `hasCustomIcon` bit set in its Finder flags field.

data fork The part of a file that contains data accessed using the File Manager. The data usually corresponds to data entered by the user; the application creating a file can store and interpret the data in the data fork in whatever manner is appropriate.

default button In an alert box or a dialog box, the button whose action is invoked when the user presses the Return key or the Enter key. The Dialog Manager automatically draws a bold outline around the default button in alert boxes; applications should draw a bold outline around

the default button in dialog boxes. The default button should invoke the preferred action, which, whenever possible, should be a “safe” action—that is, one that doesn’t cause loss of data.

desktop The working environment displayed on the Macintosh computer: the gray background area on the screen.

desktop database A Finder-maintained database of icons, file types, applications, version data, and comments for all volumes over 2 MB. Compare **Desktop file**.

Desktop file A resource file in which the Finder stores icons, file types, applications, version data, and comments for all volumes less than 2 MB. Compare **desktop database**.

Desktop Folder A directory, located at the root level of each volume, used by the Finder for storing information about the icons that appear on the desktop area of the screen. The Desktop Folder is invisible to the user. What the user sees onscreen is the union of the contents of Desktop Folders for all mounted volumes.

dial A control, similar to a scroll bar, that graphically represents the ranges of values that a user can set or that simply displays the value, magnitude, or position of something, typically in some pseudo-analog form.

dialog box A window that an application displays on the screen to solicit information from the user before the application carries out the user’s command. See also **modal dialog box**, **modeless dialog box**, and **movable modal dialog box**.

dialog color table resource A resource (of type ‘`dctb`’) that lets an application display a dialog box using colors other than the system’s default window colors.

Dialog Manager A collection of routines that applications use to implement alerts and dialog boxes.

dialog record A data structure of type `DialogRecord` that the Dialog Manager uses to create dialog boxes and alerts.

dialog resource A resource (of type ‘`DLOG`’) that specifies the window type, display rectangle, and item list for a dialog box.

GLOSSARY

disabled item In an alert box or a dialog box, an item for which the Dialog Manager does not report user events. An example of a disabled item is static text, which typically does not respond to clicks.

disk-inserted event An event indicating that a disk has been inserted into a disk drive.

display rectangle A rectangle that defines the size and location of an item in an alert box or a dialog box. The display rectangle is specified in an item list and uses coordinates local to the alert box or dialog box.

divider A gray line used in menus to separate groups of menu items.

document window A window in which the user enters text, draws graphics, or otherwise enters or manipulates data.

drag region The area occupied by a window's title bar, except for the close box and zoom box. The user can move a window on the desktop by dragging the drag region.

edition The data written to an edition container by a publisher. A publisher writes data to an edition whenever a user saves a document that contains a publisher, and subscribers in other documents may read the data from the edition whenever it is updated.

enabled item In an alert box or a dialog box, an item for which the Dialog Manager reports user events. For example, the Dialog Manager reports clicks in an enabled OK button.

event The means by which the Event Manager communicates information about user actions, changes in the processing status of the application, and other occurrences that require a response from the application.

event filter function An application-defined routine that supplements the Dialog Manager's ability to handle events—for example, an event filter function can test for disk-inserted events and can allow background applications to receive update events.

Event Manager The collection of routines that an application can use to receive information about actions performed by the user, to receive

notice of changes in the processing status of the application, and to communicate with other applications.

event mask An integer with one bit position for each event type. You specify an event mask as a parameter to Event Manager routines to specify the event types you want your application to receive, thereby disabling (or “masking out”) the events you are not interested in receiving.

event record A data structure of type `EventRecord` that your application uses when retrieving information about an event. The Event Manager returns, in an event record, information about what type of event occurred (a mouse click or keypress, for example) and additional information associated with the event.

Extensions folder A directory located in the System Folder for storing system extension files such as printer and network drivers and files of types 'INIT', 'scri', and 'appe'.

file A named, ordered sequence of bytes stored on a Macintosh volume, divided into a data fork and a resource fork.

Finder An application that works with the system software to keep track of files and manage the user's desktop display.

Fonts folder A directory located in the System Folder for storing fonts.

foreground process The process currently interacting with the user; it appears to the user as the active application. The foreground process displays its menu bar, and its windows are in front of the windows of other applications. Compare **background process**.

frame The part of a window drawn automatically by the Window Manager, namely, the title bar, including the close box and zoom box, and the window's outline.

global coordinate system The coordinate system that represents all potential QuickDraw drawing space. The origin of the global coordinate system—that is, the point (0,0)—is at the upper-left corner of the main screen. Compare **local coordinate system**.

GLOSSARY

graphics port A complete, individual drawing environment with an independent coordinate system. Each window is drawn in a graphics port.

gray area The area within a scroll bar, excluding the scroll arrows and the scroll box. When the user clicks the gray area of a scroll bar, the application moves the displayed area of the document by an entire window less one line (or column, row, or character).

gray region A region that represents all available desktop area—that is, a collection of rounded-corner rectangles representing the display areas of all monitors available to a computer.

grow image An outline of a window's new frame, drawn on the screen while the user is resizing the window with the size box.

help balloon A rounded-rectangle window that contains explanatory information for the user. With tips pointing at the objects they annotate, help balloons look like bubbles used for dialog in comic strips. Help balloons are turned on by the user from the Help menu; when Balloon Help assistance is on, a help balloon appears whenever the user moves the cursor over an area that is associated with it.

hierarchical menu A menu to which a submenu is attached.

high-level event An event sent from one application to another requesting transfer of information or performance of some action.

high-level event queue A separate queue that the Event Manager maintains to store high-level events transmitted to an application. The Event Manager maintains a high-level event queue for each open application capable of receiving high-level events.

hot spot A point that the mouse driver uses to align the cursor with the mouse location.

icon An image that represents an object, a concept, or a message.

icon family The set of icons that represent an object—such as an application or a document—displayed by the Finder. An entire icon family consists of large (32-by-32 pixel) and small

(16-by-16 pixel) icons, each with a mask, and each available in three different versions of color: black and white, 4 bits of color data per pixel, and 8 bits of color data per pixel.

inactive control A control that has no meaning or effect in the current context—for example, the scroll bars in an empty window. The Control Manager dims inactive controls or otherwise visually indicates their inactive state.

inactive window A window in which the user is not working.

indicator A moving part in a dial or slider control. A user moves an indicator to set a value, and an application moves it to indicate the current setting of the control. In a scroll bar, the scroll box is the indicator.

item color table resource A resource (of type 'ictb') that an application can use to display an alert box or a dialog box with items using a typeface, font style, font size, or colors other than the system's default font and colors. (For an application to use a nonstandard typeface, font style, or font size, the user must have a color monitor.)

item list A resource (of type 'DITL') that specifies the items—such as buttons and static text—to display in an alert box or a dialog box.

item number An integer that identifies an item in either a menu or a dialog box. Menu items are assigned item numbers starting with 1 for the first menu item in the menu, 2 for the second menu item in the menu, and so on, up to the number of the last menu item in the menu. Dialog items are assigned numbers that correspond to the item's position in its item list. For example, the first item listed in a dialog item list is item number 1.

keyboard equivalent A keyboard combination of one or more modifier keys and another key that invokes a corresponding menu command when pressed by the user.

key-down event An event indicating that the user pressed a key on the keyboard.

key-up event An event indicating that the user released a key on the keyboard.

GLOSSARY

local coordinate system The coordinate system defined by the port rectangle of a graphics port. When the Window Manager creates a window, it places the origin of the local coordinate system at the upper-left corner of the window's port rectangle. Compare **global coordinate system**.

location name An identifier for the network location of the computer on which a PPC port resides. A location name consists of an object string, a type string, and a zone.

low-level event The type of event returned by the Event Manager to report very low level hardware and software occurrences. Low-level events report actions by the user, changes in windows on the screen, and that the Event Manager has no other events to report. Compare **high-level event, operating-system event**.

major switch A change of the foreground process. The Process Manager switches the context of the foreground process with the context of a background process (including the A5 worlds and low-memory global variables) and brings the background process to the front, sending the previous foreground process to the background. See also **context**.

menu A user interface element you can use in your application to allow the user to view or choose an item from a list of choices and commands that your application provides. See also **hierarchical menu, pop-up menu, pull-down menu, and submenu**.

menu bar A white rectangle that is tall enough to display menu titles in the height of the system font and system font size, and with a black lower border that is one pixel tall. The menu bar extends across the top of the startup screen and contains the title of each available pull-down menu.

menu bar definition function A function that draws the menu bar and performs most of the drawing activities related to the display of menus when the user moves the cursor between menus. This function, in conjunction with the menu definition procedure, defines the general appearance and behavior of menus.

menu bar entry A menu color entry record that contains 0 in both the `mctID` and `mctItem` fields. A menu bar entry defines the color for an application's menu bar and defines default colors for its menu titles, menu items, and background color of menus.

menu bar resource A resource (of type 'MBAR') that specifies the order and resource ID of each menu in a menu bar.

menu color entry record A data structure of type `MCEnter` that defines the colors for an application's menu bar, menus, or menu items. The first two fields of a menu color entry record, `mctID` and `mctItem`, define whether the entry is a menu bar entry, a menu title entry, or a menu item entry.

menu color information table An array of menu color entry records, maintained by the Menu Manager, that define the standard color for the menu bar, titles of menus, text and characteristics of menu items, and background color of a displayed menu. If you do not add any entries to this table, the Menu Manager draws your menus using the default colors, black on white.

menu color information table resource A resource (of type 'mctb') that specifies the colors for an application's menu bar, menus, and menu items.

menu definition procedure A procedure that performs all the drawing of menu items within a specific menu. This procedure, in conjunction with the menu bar definition function, defines the general appearance and behavior of menus.

menu ID A number that you assign to a menu in your application. Each menu in your application must have a unique menu ID.

menu item In a menu, a rectangle with text and other characteristics identifying a command that the user can choose.

menu item entry A menu color entry record that contains nonzero values in both the `mctID` and `mctItem` fields. A menu item entry defines colors for the mark, text, and keyboard equivalent of items in a specific menu. It also defines the default background color of a menu.

GLOSSARY

menu list A data structure that contains handles to the menu records of one or more menus (although a menu list can be empty). Compare **current menu list**.

Menu Manager The collection of routines that an application can use to create, display, and manage its menus.

menu record A data structure of type `MenuInfo` that the Menu Manager uses to maintain information about a menu.

menu resource A resource (of type 'MENU') that specifies the menu title and the individual characteristics of items in a menu.

menu title entry A menu color entry record that contains a nonzero value in the `mctID` field and contains 0 in the `mctItem` field. A menu title entry defines colors for the title, items, and background color of a specific menu. It also defines the default menu bar color.

minimum partition size The actual partition size limit below which an application cannot run.

minor switch A change in the context of a process. The Process Manager switches the context of a process to give time to a background process without bringing the background process to the front.

modal dialog box A dialog box that puts the user in the state or “mode” of being able to work only inside the dialog box. A modal dialog box resembles an alert box. The user cannot move a modal dialog box and can dismiss it only by clicking its buttons. See also **modeless dialog box** and **movable modal dialog box**.

modeless dialog box A dialog box that looks like a document window without a size box or scroll bars. The user can move a modeless dialog box, make it inactive and active again, and close it like any document window. See also **modal dialog box** and **movable modal dialog box**.

modifier keys The Shift, Option, Command, Control, and Caps Lock keys.

mouse-down event An event indicating that the user pressed the mouse button.

mouse location The location of the cursor at the time the event occurred.

mouse-moved event An event indicating that the cursor is outside of a specified region.

mouse-up event An event indicating that the user released the mouse button.

movable modal dialog box A modal dialog box that has a title bar (with no close box) by which the user can drag the dialog box. See also **dialog box**, **modal dialog box**, and **modeless dialog box**.

note alert An alert box that informs users of a minor mistake that won't have any disastrous consequences if left as is. Usually a note alert simply offers information, and the user responds by clicking the OK button. A note alert is identified by an icon bearing a face and a cartoonlike dialog balloon in the upper-left corner of the alert box. See also **caution alert** and **stop alert**.

null event An event indicating that no events of the requested types exist in the application's event stream.

offset point The point in a region whose horizontal and vertical offsets from the upper-left corner of the region's enclosing rectangle are the same as the offsets of a specified point. The `DrayGrayRgn` function uses an offset point to limit the motion of a region and to calculate the distance a region has moved.

operating-system event An event returned by the Event Manager to communicate information about changes in the operating status of applications (suspend and resume events) and to report that the user has moved the cursor outside of an area specified by the application (mouse-moved events). Compare **low-level event**, **high-level event**.

Operating System Event Manager The collection of low-level routines that manage the Operating System event queue.

Operating System event queue A queue that the Operating System Event Manager creates and maintains. The Operating System Event Manager detects and reports low-level hardware-related events such as mouse clicks, keypresses, and disk insertions and places these events in the Operating System event queue.

GLOSSARY

part code An integer from 1 through 253 that stands for a particular part of a control. The `FindControl` and `TrackControl` functions return a part code to indicate the location of the cursor when the user presses the mouse button.

pop-up menu A menu that appears elsewhere than the menu bar. The Control Manager provides a control definition function for applications to use when implementing pop-up menus.

port name A unique identifier for a particular application on a computer, used for the purposes of communication between applications. A port name consists of a name string, a type string, and a script code.

port rectangle An entry in the graphics port data structure, described in *Inside Macintosh: Imaging*. Ordinarily, the port rectangle represents the area of a graphics port available for drawing—that is, the content region of a window.

Preferences folder A directory located in the System Folder for holding files that record users' configuration settings for applications on a particular Macintosh computer.

preferred partition size The partition size at which an application can run most effectively. The Operating System attempts to secure this partition size upon launch of the application.

PrintMonitor Documents folder A directory located in the System Folder for storing spooled documents waiting to be printed.

process An open application or, in some cases, an open desk accessory. (Only desk accessories that are not opened in the context of another application are considered processes.)

process serial number A number assigned by the Process Manager to identify a particular instance of an application during a single boot of the local machine.

pull-down menu A menu that is identified by a menu title (a word or an icon) in the menu bar.

query document A file of file type 'query' containing commands and data in a format appropriate for a database or other data source. An application uses high-level Data Access Manager routines to open a query document.

radio button A control that appears onscreen as a small circle. A radio button displays one of two settings: on (indicated by a black dot inside the circle) or off. A radio button is always a part of a group of related radio buttons in which only one button can be on at a time. When the user clicks an unmarked radio button, the application turns that button on and turns the other buttons in its group off.

Rescued Items from volume name folder A directory located in the Trash directory and created by the Finder at system startup, restart, or shutdown only when it finds items in the Temporary Items folder, usually after a system crash. The Rescued Items from *volume name* folder is named for the volume on which the Temporary Items folder exists. When a user empties the Trash, all Rescued Items folders disappear.

resource Any data stored according to a defined structure in a resource fork of a file; the data in a resource is interpreted according to its resource type.

resource fork The part of a file that contains the files' resources. A resource fork consists of a resource map and resources.

resource ID A number that identifies a specific resource of a given resource type.

resource type A sequence of four characters that uniquely identifies a specific type of resource.

resume event An event indicating that an application has been switched back into the foreground and can resume interacting with the user.

return receipt A high-level event that indicates whether the other application accepted the high-level event sent to it by your application.

scroll arrow An arrow at either end of a scroll bar. When the user clicks a scroll arrow, the application moves a document or list one line (or some similar measure) in the direction of the arrow. When the user holds the mouse button down while the cursor is over a scroll arrow, the application moves the document or list continuously in the direction of the arrow.

GLOSSARY

scroll bar A control with which the user can change the portion of a document displayed within a window. A scroll bar is a light gray rectangle with scroll arrows at each end. Windows can have a horizontal scroll bar, a vertical scroll bar, or both. A vertical scroll bar lies along the right side of a window. A horizontal scroll bar runs along the bottom of a window. Inside the scroll bar is a rectangle called the scroll box. The rest of the scroll bar is called the gray area. The user can move through a document by manipulating the parts of the scroll bar.

scroll box A box that slides up and down or back and forth across a scroll bar. The position of the scroll box in a scroll bar indicates the position of the window contents relative to the entire document. When the user drags the scroll box, the application displays a different portion of the document.

signature A resource whose type is defined by a four-character sequence that uniquely identifies an application to the Finder. A signature is located in an application's resource fork.

size box A box in the lower-right corner of windows that can be resized. Dragging the size box resizes the window.

size region The area occupied by a window's size box. See also **size box**.

size resource A resource (of type 'SIZE') that specifies the operating characteristics, minimum partition size, and preferred partition size of an application.

slider A control, such as a scroll bar, that graphically represent the ranges of values that a user can set or that simply displays the value, magnitude, or position of something, typically in some pseudo-analog form.

standard control definition functions Three control definition functions, stored as 'CDEF' resources in the System file. The 'CDEF' resource with resource ID 0 defines the look and behavior of buttons, checkboxes, and radio buttons; the 'CDEF' resource with resource ID 1 defines the look and behavior of scroll bars; and the 'CDEF' resource with resource ID 63 defines the look and behavior of pop-up menus.

standard state The size and location that an application deems the most convenient for a window.

Startup Items folder A directory located in the System Folder for storing applications and desk accessories that the user wants started up every time the Finder starts up.

stationery pad A document that a user creates to serve as a template for other documents. The Finder tags a document as a stationery pad by setting the `isStationery` bit in the Finder flags field of the file's file information record. An application that is asked to open a stationery pad should copy the template's contents into a new document and open the document in an untitled window.

stop alert An alert box that informs the user of a problem or situation so serious that the user's desired action cannot be completed. Stop alerts typically have only a single button (OK), because all the user can do is acknowledge that the action cannot be completed. A stop alert is identified by an icon of an upraised hand in the upper-left corner of the alert box. See also **caution alert** and **note alert**.

structure region The entire screen area occupied by a window, including both the window frame and the content region.

submenu A menu that is attached to another menu.

suspend event An event indicating that the execution of your application is about to be suspended as the result of a major switch. The application is suspended at the application's next call to `WaitNextEvent` or `EventAvail`.

system alert sound A sound resource that is stored in the System file and played whenever system software or an application uses the Sound Manager procedure `SysBeep`. With the Sound control panel, the user can select which sound to use.

System file A file, located in the System Folder, that contains the basic system software plus some system resources, such as sound and keyboard resources. The System file behaves like a folder in this regard: although it looks like a suitcase icon,

GLOSSARY

double-clicking it opens a window that reveals movable resource files (such as sounds, keyboard layouts, and script system resource collections) stored in the System file.

System Folder A directory containing the software that Macintosh computers use to start up. The System Folder includes a set of folders for storing related files, such as preferences files that an application might need when starting up.

Temporary Items folder A directory located at the root level of a volume for storing temporary buffer files created by applications. The Temporary Items folder is invisible to the user.

text style table In an item color table resource, a specification for the typeface, font style, font size, and color of text in an editable text item or a static text item.

title bar The bar at the top of a window that displays the window name, contains the close and zoom boxes, and indicates whether the window is active.

Toolbox Event Manager See **Event Manager**.

Trash folder A directory at the root level of a volume for storing files that the user has moved to the Trash icon. After opening the Trash icon, the user sees the collection of all items that the user has moved to the Trash icon—that is, the union of appropriate Trash directories from all mounted volumes. A Macintosh computer set up to share files among users in a network environment maintains separate Trash subdirectories for remote users within its shared Trash directory. The Finder empties a Trash directory (or, in the case of a file server, a Trash subdirectory) only when the user of that directory chooses the Empty Trash command.

update event An event indicating that the contents of a window need updating.

update region A region maintained by the Window Manager that includes the parts of a window's content region that need updating. The Event Manager generates update events as necessary, based on the contents of the update region, telling your application to update a window.

user state The size and location that the user has established for a window.

variation code A number that selects among variations supported by a single window definition function or control definition function. The variation code is stored in the low-order 4 bits of the window definition ID or control definition ID. See also **control definition function, control definition ID, window definition function, and window definition ID**.

virtual key code A value that represents the key pressed or released by the user; this value is always the same for a specific physical key on a keyboard. Compare **character code**.

visible region The part of a window's graphics port that's actually visible on the screen—that is, the part that's not covered by other windows.

window An area on the screen that displays information, including user documents as well as communications such as alert boxes and dialog boxes. The user can open or close a window; move it around on the desktop; and sometimes change its size, scroll through it, and edit its contents.

window color table The data structure in which the Window Manager stores the colors to be used for drawing a window's frame and for highlighting selected text.

window definition function A function that defines the general appearance and behavior of a window. The Window Manager calls the window definition function to draw the window's frame, determine what region of the window the cursor is in, draw the window's size box, draw the window's zoom box, move and resize the window, and calculate the window's structure and content regions.

window definition ID An integer that specifies the resource ID of a window definition function in the upper 12 bits and an optional variation code in the lower 4 bits. When creating a new window, your application supplies a window definition ID either as a field in the 'WIND' resource or as a parameter to the `NewWindow` or `NewCWindow` function.

GLOSSARY

window list A list maintained by the Window Manager of all windows on the desktop. The frontmost window is first in the window list, and the remaining windows appear in the order in which they are layered on the desktop.

Window Manager port A graphics port that represents the desktop area on the main monitor—that is, a rounded-corner rectangle that occupies all of the main monitor except for the area occupied by the title bar.

window origin The upper-left corner of a window. Usually specified as (0,0), the window origin is expressed in coordinates local to the window.

window record A data structure of type `WindowRecord` (or `CWindowRecord`) in which the Window Manager stores a window's characteristics, including the window's graphics port, title, visibility status, and control list.

window region Special-purpose region of a window. See also **close region**, **content region**, **drag region**, **size region**, and **zoom region**.

window type A collection of characteristics—such as the shape of the window's frame and the features of its title bar—that describe a window.

zoom box A box in the right side of a window's title bar that the user can click to alternate between two different window sizes (the user state and the standard state).

zoom region The area occupied by a window's zoom box. See also **zoom box**.

Index

Symbols

'****' file type 7-20
'????' file type 7-20

Numerals

4-bit color icons 7-11
8-bit color icons 7-11
16-by-16 pixel (small) icons 7-11, 7-15
32-by-32 pixel (large) icons 7-11, 7-13

A

About command (Apple menu) 3-21 to 3-22, 3-45
acceptAppDiedEvents flag 2-118
AcceptHighLevelEvent function 2-69, 2-70 to 2-71,
2-87, 2-90 to 2-92
acceptSuspendResumeEvents flag 2-117
ACount global variable 6-172
'actb' resource type 6-157 to 6-158
action procedures
for buttons, checkboxes, and radio buttons 5-36
changing 5-102
creating 5-115 to 5-117
defined 5-35
for pop-up menus 5-36 to 5-37
for scroll bars 5-58 to 5-61
specifying 5-91, 5-92
activate events
in alert boxes 6-82
deactivating windows for alert and dialog
boxes 6-64 to 6-66
defined 2-8
in dialog boxes 6-85, 6-97 to 6-100
handling 2-50 to 2-55, 4-50 to 4-53
and windows 4-42
active controls 5-11 to 5-13, 6-13 to 6-14
active windows 4-6 to 4-7
AddResMenu procedure. *See* AppendResMenu procedure
AEIMP (Apple Event Interprocess Messaging
Protocol) 2-13, 2-67
AEProcessAppleEvent function 2-68, 2-78
AESend function 2-73, 2-78, 2-100
A5 world

and context switching 2-16
size of 2-32
alert boxes
accessing menus from 6-68 to 6-73
creating 6-18 to 6-23
default colors of, changing 6-157 to 6-158
defined 6-6
dialog boxes, as distinguished from 6-6 to 6-8
displaying 6-22, 6-61 to 6-75
event filter function for 6-86 to 6-89, 6-145 to 6-147
events in 2-29 to 2-30, 6-81 to 6-82
items in. *See* items in alert and dialog boxes
stages for 6-20 to 6-22, 6-150 to 6-151
types of 6-8 to 6-9
as windows 6-15 to 6-17
window types for 4-9
alert color table resources 6-157 to 6-158
Alert function 6-106 to 6-108
alert resources
defined 6-15
example of 6-20, 6-21
Rez input format for 6-19 to 6-22
Rez output format for 6-150 to 6-151
alerts
creating 6-18 to 6-23, 6-105 to 6-112
defined 6-5
defining alert sounds for 6-22, 6-144 to 6-145
displaying 6-61 to 6-75
events in 6-81 to 6-82
stages for 6-20 to 6-22, 6-150 to 6-151
types of 6-8 to 6-9
using the system alert sound 6-8
alert sounds
creating 6-18 to 6-22
defined 6-6
defining 6-22, 6-144 to 6-145
specifying 6-151
stages for 6-20 to 6-22, 6-150 to 6-151
and the system alert sound 6-8
aliases
defined 7-39
resolving 7-39 to 7-41, 7-51 to 7-53
alias files 7-39
alias records 7-40
alias types 7-40
'alis' resource type 7-40
'ALRT' resource type. *See* alert resources
altDBoxProc window type 4-9
'amnu' folder type 7-54

INDEX

ANumber global variable 6-172
'appe' file type 7-44
AppendDITL procedure 6-54, 6-125 to 6-127
AppendMenu procedure 3-64 to 3-67, 3-124 to 3-125
AppendResMenu procedure 3-20, 3-68 to 3-70, 3-128 to 3-129
Apple Event Interprocess Messaging Protocol (AEIMP) 2-13, 2-67
Apple events
 application sending to itself 3-71
 defined 2-13
 and the Finder 7-25 to 7-26
 handling 2-78
 as high-level events 2-67 to 2-69
 Open Documents 7-20
 sending 2-78
 in response to menu commands 3-71
Apple menu 3-20
 About command 3-21 to 3-22, 3-45
 accessing from dialog boxes 6-68 to 6-73
 adding items to 3-68 to 3-69
 creating 3-43 to 3-44
 handling 3-80 to 3-81
Apple Menu Items folder
 adding items from, to Apple menu 3-20 to 3-21
 alias type for 7-40
 defined 7-43
 finding 7-54
'APPL' file type 7-10
application-defined items
 creating 6-56 to 6-61
 specifying in alert or dialog boxes 6-29 to 6-30, 6-155
application heap 2-32
application icons. *See also* icon families
 creating 7-10 to 7-17
 default 7-12
Application menu 3-33
 accessing from alert and dialog boxes 6-68 to 6-69
 Hide Others command 3-33
application-missing message string resources 7-27 to 7-30, 7-68 to 7-69
applications
 alias type for 7-40
 in Apple Menu Items folder 7-43
 creating icons for 7-11 to 7-17
 default icon for 7-12
 launching from the Finder 7-25 to 7-26
 sharing 2-68
 signatures for 7-8 to 7-10
 switching between 2-5
application-unavailable alert box messages 7-27 to 7-30
arrow cursor 2-63
arrows, in scroll bars. *See* scroll arrows
'****' file type 7-20
AtMenuBottom global variable 3-151

auto-key events 2-38
auto-key threshold rate 2-38
A/UX and cancel events 2-46
AuxCtlRec data type 5-76 to 5-77, 5-107
auxiliary control records 5-76 to 5-77, 5-107
auxiliary window record 4-21, 4-73 to 4-74
AuxWinRec data type 4-73 to 4-74

B

background applications, and Extensions folder 7-44
background processes 2-4
Balloon Help online assistance, for icons 7-38. *See also* help balloons
BeginUpdate procedure 2-47, 4-50, 4-106 to 4-107
'BNDL' resource type 7-20 to 7-25, 7-65 to 7-68
BringToFront procedure 4-90
bundle bit 7-34
bundle resources 7-20 to 7-25, 7-45, 7-65 to 7-68
Button function 2-108
buttons
 active 5-11 to 5-13
 control definition ID for 5-14
 creating, in windows 5-17 to 5-20
 default 6-10 to 6-11, 6-22, 6-30 to 6-31, 6-56 to 6-61
 defined 5-5
 events in 5-31 to 5-37, 6-78
 inactive 5-11 to 5-13
 part code for 5-32
 specifying in alert or dialog boxes 6-29 to 6-30, 6-153
 titles for 6-37 to 6-39

C

CalcMenuSize procedure 3-143, 5-28
CalcVisBehind procedure 4-119
CalcVis procedure 4-119
canBackground flag 2-117
cancel events 2-46 to 2-47
Can't Undo command (Edit menu) 3-24, 3-25
Caps Lock key 2-20
caret, time between blinks of 2-113
catalog files
 defined 7-5
 Finder information in 7-32 to 7-34, 7-46 to 7-51
CautionAlert function 6-111
caution alerts
 creating with the CautionAlert function 6-111
 defined 6-9
'cctb' resource type 5-121 to 5-123
'CDEF' resource type 5-14, 5-109 to 5-115
character codes 2-40

INDEX

- checkboxes
 - active 5-11 to 5-13
 - changing setting and display of 5-38 to 5-39
 - control definition ID for 5-14
 - defined 5-5 to 5-6
 - events in 6-78
 - in windows 5-31 to 5-32, 5-38 to 5-39
 - inactive 5-11 to 5-13
 - part code for 5-32
 - specifying in alert or dialog boxes 6-29 to 6-30, 6-153
- CheckItem procedure 3-61 to 3-62, 3-136
- CheckUpdate function 4-116
- 'cicn' resource type 7-64
 - specifying a menu item's 3-62, 3-154
- Clear command (Edit menu) 3-25, 6-69
- ClearMenuBar procedure 3-110
- ClipAbove procedure 4-116 to 4-117
- Clipboard 3-24
 - converting data to and from 2-58 to 2-60
 - Hide Clipboard command (Edit menu) 3-25
 - Show Clipboard command (Edit menu) 3-25
- close box 4-6
- Close command (File menu) 3-23
- CloseDialog procedure 6-119 to 6-120
- close region 4-12
- CloseWindow procedure 4-60, 4-104 to 4-105
- closing windows 4-60 to 4-62
 - routines for 4-103 to 4-106
- 'CNTL' resource type
 - example of 5-18, 5-21, 5-23, 5-26
 - Rez input format for 5-18 to 5-24, 5-25 to 5-28
 - Rez output format for 5-118 to 5-121
- Color control panel 4-20, 4-65
- color flag 7-48
- color graphics ports 4-20
- color icon resources 3-46, 3-62, 7-64
- color icons 7-11, 7-13 to 7-16
- Color QuickDraw
 - checking for
 - when creating a window 4-77
 - when zooming windows 4-54
 - and color window records 4-65
 - coordinate systems in 4-17 to 4-18
 - creating color windows 4-20 to 4-21
 - and the Window Manager port 4-74
- colorReserved flag 7-48
- colors
 - in alert boxes and dialog boxes 6-156 to 6-164
 - in controls 5-5
 - Label menu commands for 7-16
 - in menus 3-46, 3-62, 3-98 to 3-102
 - in windows 4-20 to 4-21
- ColorSpec data type 4-72, 5-78 to 5-79
- color window records 4-65 to 4-68
- Command key 2-20
- Command-key equivalents. *See* keyboard equivalents
- Command-Shift-number key sequences 2-39, 2-86
- content region
 - defined 4-6, 4-12
 - drawing 4-39 to 4-40
 - updating 4-40 to 4-41, 4-48 to 4-50
- context of a process, switching 2-15 to 2-16
- control color table records 5-77 to 5-80
- control color table resources 5-121 to 5-123
- control color tables 6-160 to 6-162
- control definition functions
 - custom 5-109 to 5-115
 - defined 5-14
 - for pop-up menus 5-14, 5-36
 - standard 5-14
- control definition IDs
 - for buttons 5-14
 - for checkboxes 5-14
 - for custom controls 5-109 to 5-110
 - defined 5-14
 - for pop-up menus 5-14
 - for radio buttons 5-14
 - for scroll bars 5-14
 - specifying 5-18, 5-19, 5-25, 5-83 to 5-84, 5-120
- Control key 2-20
- control list 4-14
- Control Manager 5-3 to 5-135
 - application-defined routines for 5-109 to 5-117
 - data structures in 5-72 to 5-80
 - and Dialog Manager 5-3, 5-5, 5-16, 5-29, 5-31, 6-78
 - and Event Manager 5-3
 - and List Manager 5-3
 - localization guidelines 5-15, 5-19 to 5-20, 5-85, 5-120
 - and Resource Manager 5-3
 - resources for 5-117 to 5-123. *See also* control color tables; control definition functions; control resources;
 - routines in 5-80 to 5-117
 - user interface guidelines 5-5 to 5-13, 5-52 to 5-53
 - and Window Manager 5-3
- control panels, installing and removing 7-41
- Control Panels folder
 - alias type for 7-40
 - defined 7-43
 - finding 7-54
- ControlRecord data type 5-73 to 5-75
- control records 5-73 to 5-75
- control resources
 - example of 5-18, 5-21, 5-23, 5-26
 - Rez input format for 5-18 to 5-24, 5-25 to 5-28
 - Rez output format for 5-118 to 5-121
- controls
 - action procedures for 5-91, 5-102, 5-115 to 5-117
 - activating 5-13
 - active 5-11 to 5-13, 6-13

INDEX

- in alert and dialog boxes 6-29 to 6-30, 6-154
- colors in 5-5, 5-101, 5-121 to 5-123
- control definition IDs for 5-18, 5-19, 5-25, 5-83 to 5-84, 5-120
- custom. *See* custom controls
- defined 5-3
- dragging 5-35, 5-99 to 5-100, 5-114 to 5-115
- drawing 5-17, 5-85 to 5-88
- events in 5-88 to 5-93, 6-78
- highlight states of 5-35, 5-98 to 5-99
- inactive 5-13, 6-13, 6-74
- indicators in. *See* indicators, in controls
- invisible 5-18, 5-19, 5-25, 5-83, 5-97, 5-119
- mouse events in 5-11 to 5-13, 5-30 to 5-70
- moving 5-65 to 5-70, 5-97 to 5-98
- part codes for 5-31 to 5-32
- pop-up menus 6-42 to 6-44
- rectangles for 5-18 to 5-19, 5-22 to 5-23, 5-25 to 5-26, 5-82, 5-118. *See also* display rectangles
- reference values for
 - changing 5-105 to 5-106
 - determining 5-105
 - specifying 5-18, 5-25, 5-84, 5-120
- removing 5-108 to 5-109
- resizing 5-65 to 5-70, 5-98
- resources for. *See* control resources
- settings of
 - changing 5-11, 5-37 to 5-43, 5-61, 5-65 to 5-70, 5-93 to 5-102
 - determining 5-37 to 5-43, 5-102 to 5-107
 - specifying initial 5-18 to 5-19, 5-21 to 5-23, 5-25 to 5-28, 5-83, 5-118 to 5-119
- standard 5-4, 5-15 to 5-28, 5-81 to 5-85
- text in 5-18, 5-19 to 5-20, 5-25
- titles of
 - changing 5-96
 - determining 5-104 to 5-105
 - specifying 5-18, 5-19 to 5-20, 5-25, 5-83, 5-85, 5-120, 5-121
- types of 5-4 to 5-13. *See also* buttons; checkboxes; custom controls; pop-up menus; radio buttons; scroll bars
- updating 5-29 to 5-30
- visible 5-18, 5-19, 5-25, 5-83, 5-119
- in windows 4-14 to 4-15, 4-23, 5-82
- cooperative multitasking 2-10
- coordinate systems 4-17 to 4-18
- Copy command (Edit menu) 3-25, 6-69
- CountDITL function 6-128
- CountMItems function 3-81, 3-141
- Create Publisher command (Edit menu) 3-25
- creators
 - assigning 7-33 to 7-34, 7-47 to 7-49
 - defined 7-9 to 7-10
- CtlCTab data type 5-77 to 5-80

- 'ctrl' folder type 7-54
- current menu list 3-40
- current process 2-28
- cursors
 - adjusting 2-65 to 2-67
 - arrow 2-63
 - cross 2-63
 - I-beam 2-63
 - plus 2-63
 - setting the appearance of 2-62
 - wristwatch 2-63
- custom alert boxes
 - creating with the `Alert` function 6-106 to 6-108
 - defined 6-9
- custom controls 5-11, 5-109 to 5-115
- customized icons 7-17 to 7-18
- Cut command (Edit menu) 3-25, 6-69
- CWindowPeek data type 4-65
- CWindowPtr data type 4-65
- CWindowRecord data type 4-65 to 4-68

D

- DABeeper global variable 6-172
- DAStrings global variable 6-172
- data forks 1-11
- dBoxProc window type 2-16, 4-9, 6-25
- 'dctb' resource type 6-156 to 6-157
- default buttons 6-10 to 6-11, 6-22, 6-30 to 6-31, 6-56 to 6-61
- DeleteMCEntries procedure 3-147
- DeleteMenuItem procedure 3-127 to 3-128
- DeleteMenu procedure 3-109 to 3-110
- DelMCEntries procedure. *See* DeleteMCEntries procedure
- DelMenuItem procedure. *See* DeleteMenuItem procedure
- desk accessories
 - handling events in 2-36, 2-87, 2-95
 - and System 7 7-13
- desk accessory resource. *See* 'DRVR' resource type
- 'desk' folder type 7-54
- DeskHook global variable 4-75
- DeskPattern global variable 4-113
- desktop 7-3
- desktop database 7-5, 7-45 to 7-46
- Desktop file 7-5
- Desktop Folder
 - defined 7-43
 - finding 7-54
- Desktop Manager 7-45
- desktop objects 3-20
- desktop pattern 4-112
- dial controls 5-11

INDEX

- dialog boxes
 - accessing menus from 3-84, 6-68 to 6-73
 - alert boxes, as distinguished from 6-6 to 6-8
 - closing 6-100 to 6-101
 - creating 6-23 to 6-26, 6-113 to 6-119
 - default colors of, changing 6-156 to 6-157
 - defined 6-5
 - displaying 6-61 to 6-75
 - disposing of 6-113, 6-119 to 6-120
 - event filter function for 6-86 to 6-89
 - events in 2-25, 2-29 to 2-30, 6-82 to 6-100, 6-135 to 6-143
 - examples of 1-9
 - items in. *See* items in alert and dialog boxes
 - types of 6-9 to 6-12
 - as windows 6-15 to 6-17
 - window types for 4-9 to 4-10
- dialog color table resources 6-75, 6-156 to 6-157
- DialogCopy procedure 6-133
- DialogCut procedure 6-132 to 6-133
- DialogDelete procedure 6-134
- Dialog Manager 6-5 to 6-172
 - application-defined routines for 6-143 to 6-147
 - and Control Manager 5-3, 5-5, 5-16, 5-29, 5-31, 6-78
 - data structures in 6-101 to 6-102
 - initializing 6-102 to 6-105
 - localization guidelines for 6-34 to 6-35, 6-39, 6-40, 6-80, 6-130
 - and Menu Manager 6-68 to 6-73
 - resources in 6-147 to 6-164. *See also* alert color table resources; alert resources; dialog color table resources; dialog resources; item color table resources; item list resources
 - routines in 6-102 to 6-147
 - testing for availability of AppendDITL, ShortenDITL, and CountDITL routines 6-18
 - and TextEdit 6-79 to 6-80
 - user interface guidelines for 6-8 to 6-12, 6-31 to 6-34, 6-37 to 6-41, 6-42, 6-62 to 6-64
 - and Window Manager 4-13 to 4-14, 6-15 to 6-16
- DialogPaste procedure 6-133 to 6-134
- DialogPeek data type 6-102
- DialogPtr data type 6-102
- DialogRecord data type 6-101 to 6-102
- dialog records 6-101 to 6-102
- dialog resources
 - defined 6-15
 - example of 6-24
 - Rez input format for 6-24 to 6-26
 - Rez output format for 6-148 to 6-149
- DialogSelect function 2-29, 6-80, 6-89 to 6-93, 6-139 to 6-141
- DIBadMount function 2-56
- DInfo data type 7-50
- directories, finding system-related 7-53 to 7-56
- directory information record 7-50
- disabled constant 3-8
- disabled items 6-13
- DisableItem procedure 3-58 to 3-59, 3-131 to 3-132
- 'disk' file type 7-20
- disk-inserted events
 - in alert and dialog boxes 6-87
 - handling 2-55 to 2-56
 - and the ModalDialog procedure 2-56
 - and standard file dialog boxes 2-55
- disks, opening 7-20
- display rectangles, for items in alert and dialog boxes 6-29, 6-32 to 6-35
- DispMCInfo procedure. *See* DisposeMCInfo procedure
- DisposeDialog procedure. *See* DisposeDialog procedure
- DisposeControl procedure 5-108
- DisposeDialog procedure 6-120
- DisposeMCInfo procedure 3-145
- DisposeMenu procedure 3-140
- DisposeWindow procedure 4-105 to 4-106
- DITLMethod data type 6-51, 6-166
- 'DITL' resource type. *See* item list resources
- dividers 3-12
- DlgCopy procedure. *See* DialogCopy procedure
- DlgCut procedure. *See* DialogCut procedure
- DlgDelete procedure. *See* DialogDelete procedure
- DlgFont global variable 6-172
- DlgPaste procedure. *See* DialogPaste procedure
- 'DLOG' resource type. *See* dialog resources
- documentProc window type 4-10
- documents 5-9 to 5-10, 5-43 to 5-70
 - creating icons for 7-16 to 7-17, 7-17 to 7-18
 - creators of 7-9 to 7-10
 - default icon for 7-12
 - file types of 7-9 to 7-10, 7-18 to 7-20
 - opening from the Finder 7-25 to 7-26
 - prohibiting users from opening from Finder 7-30
 - window types for 4-8
- document windows
 - defined 4-4
 - positioning 4-30
 - saving position of 4-34
 - window types for 4-8
- doesActivateOnFGSwitch flag 2-117
- double clicks, time between 2-38, 2-113
- DragControl procedure 5-99 to 5-100
- DragGrayRgn function 4-96 to 4-98
- DragHook global variable 4-98, 4-100, 4-102, 4-104
- drag region 4-12
- DragWindow procedure 4-44, 4-94 to 4-95
- DrawControls procedure 5-87 to 5-88
- DrawDialog procedure 6-142
- DrawGrowIcon procedure 4-12, 4-39, 4-86 to 4-87
- DrawMenuBar procedure 3-51, 3-58, 3-113
- DrawNew procedure 4-117

INDEX

DrawControl procedure 5-88
'drop' alias type 7-40
drop folder, alias type for 7-40
'DRVR' resource type 3-20, 3-68, 3-129, 3-130
DXInfo data type 7-50 to 7-51

E

editable text items

events in 6-79 to 6-80
getting text from 6-48 to 6-51, 6-130 to 6-131
highlighting default text in 6-131 to 6-132
setting text in 6-131, 6-153
specifying in dialog boxes 6-29 to 6-30, 6-153

Edition Manager 2-14

editions

creating icons for 7-16
defined 7-4

Edit menu 3-24 to 3-26

accessing from alert and dialog boxes 6-68 to 6-73
adjusting 3-75 to 3-77
Can't Undo command 3-25
Clear command 3-25, 6-69
Copy command 3-25, 6-69
Create Publisher command 3-25
Cut command 3-25, 6-69
Hide Clipboard command 3-25
Paste command 3-25, 6-69
Publisher Options command 3-25
Select All command 3-25
Show Clipboard command 3-25
Subscriber Options command 3-25
Subscribe To command 3-25
Undo command 3-25, 6-69

8-bit color icons 7-11

'empt' folder type 7-54

enabled constant 3-8

enabled items 6-13

EnableItem procedure 3-58 to 3-59, 3-131

EndUpdate procedure 2-47, 2-49, 4-50, 4-107

EraseRect procedure 4-103

ErrorSound procedure 6-104

EventAvail function 2-21, 2-88 to 2-89

event classes 2-68

event filter functions 6-86 to 6-89, 6-145 to 6-147

event IDs 2-68

event loops 2-24 to 2-25

Event Manager 2-3 to 2-132. *See also* Operating System

Event Manager

application-defined routine for 2-114 to 2-115
and Control Manager 5-3
data structures in 2-79 to 2-83
initializing 2-17

and MultiFinder 2-7

and the PPC Toolbox 2-7, 2-13

and the Process Manager 2-5

routines in 2-84 to 2-113

and the Scrap Manager 2-60

testing for features 2-17

event masks

defined 2-22, 2-85

setting 2-26 to 2-29

event messages 2-19, 2-80

event queue. *See also* high-level event queue; Operating

System event queue

scanning for a cancel event in 2-46

structure of 2-83

EventRecord data type 2-79 to 2-81

event records 2-79 to 2-81

defined 2-4

and event loops 2-25

for high-level events 2-68, 2-69

events

activate 2-8, 2-50 to 2-55, 4-50 to 4-53

in alert boxes 2-29 to 2-30, 6-81 to 6-82, 6-86 to 6-89,
6-135

Apple. *See* Apple events

auto-key 2-8, 2-38

in buttons in windows 5-31 to 5-37

cancel 2-46 to 2-47

in checkboxes in windows 5-38 to 5-39

Command-period 2-46

in controls 5-11 to 5-13, 5-30 to 5-70, 5-88 to 5-93, 6-78

defined 2-4

in desk accessories 2-36

in dialog boxes 2-29 to 2-30, 6-77 to 6-100, 6-135 to
6-143

disk-inserted 2-8, 2-55 to 2-56

in editable text items 6-79 to 6-80

filter function for, in alert and dialog boxes 6-86 to
6-89, 6-145 to 6-147

first click in an inactive window 4-42

getting information about 2-18 to 2-21

in gray areas of scroll bars 5-57 to 5-61

handling 2-26

high-level. *See* high-level events

interacting with the user from the background 2-12

keyboard 2-8, 2-38 to 2-45

key-down 2-38

key-up 2-38, 2-39

low-level 2-8 to 2-9

masking out 2-27

events (*continued*)

in modal dialog boxes 6-82 to 6-89, 6-135 to 6-137

in modeless dialog boxes 2-25, 6-89 to 6-100, 6-138 to
6-141

and modifier keys 2-20 to 2-21, 2-34

mouse-down 2-8, 2-33 to 2-38

INDEX

- mouse-down in windows 4-42 to 4-45
- mouse-moved 2-12, 2-23, 2-62 to 2-67
- mouse-up 2-8, 2-33
- in movable modal dialog boxes 6-89 to 6-100, 6-138 to 6-141
- null 2-9, 2-57
- operating-system 2-10 to 2-12, 2-58 to 2-67
- in pop-up menus 6-42
 - in windows 5-31 to 5-37
- priority of 2-15
- processing 2-21 to 2-30
- in radio buttons in windows 5-31 to 5-32
- received in the background 2-12
- receiving from other applications 2-69 to 2-71
- resume 2-12, 2-60 to 2-62
- in scroll arrows 5-57 to 5-61
- in scroll bars 5-43 to 5-65
- in scroll boxes 5-53 to 5-57
- sources of 2-6
- suspend 2-12, 2-60 to 2-62
- switching contexts 2-15 to 2-16
- types of 2-5, 2-18, 2-79
- update 2-9, 2-47 to 2-50, 4-48 to 4-50
- in windows 4-21 to 4-22, 4-41 to 4-53

event types 2-5, 2-18, 2-79

EvQEl data type 2-83

exported AppleShare folder, alias type for 7-40

extended directory information record 7-50 to 7-51

extended file information record 7-49

Extensions folder

- alias type for 7-40
- defined 7-44
- finding 7-54

'extn' folder type 7-54

F

- 'faam' alias type 7-40
- 'fact' alias type 7-40
- 'fadr' alias type 7-40
- 'faet' alias type 7-40
- 'faex' alias type 7-40
- 'famn' alias type 7-40
- 'fapf' alias type 7-40
- 'fapn' alias type 7-40
- 'fash' alias type 7-40
- 'fast' alias type 7-40
- 'fasy' alias type 7-40
- 'fdrp' alias type 7-40
- 'ffil' file type 7-37

file information record 7-34, 7-47 to 7-49

File menu 3-22 to 3-24

- Close command 3-23, 7-18

- New command 3-23
- Open command 3-23
- Page Setup command 3-23
- Print command 3-23
- Quit command 3-23, 7-18
- Save As command 3-23
- Save command 3-23

file reference resources 7-18 to 7-25, 7-64 to 7-65

files. *See also* applications; documents

- data fork of 1-11
- managing 1-15
- resource fork of 1-11
- temporary 7-43
- user comments associated with 7-45

file types

- for alias files 7-40
- 'appe' 7-33, 7-47
- 'APPL' 7-10

assigning 7-9 to 7-10, 7-33 to 7-34, 7-47 to 7-49

'*****' 7-20

defining in file reference resources 7-18 to 7-25

- 'DFIL' 7-37
- 'disk' 7-20
- 'FFIL' 7-37
- 'ffil' 7-37
- 'fold' 7-20
- 'ifil' 7-37
- 'kfil' 7-37

for movable resources 7-37

opening documents of particular

- from applications 7-10
- from the Finder 7-25 to 7-26

- '????' 7-20
- 'scri' 7-44
- 'sfil' 7-37

for stationery pads 7-19

'tfil' 7-37

filter function. *See also* event filter functions

- for GetSpecificHighLevelEvent 2-92 to 2-93, 2-114 to 2-115

FindControl function 5-33 to 5-35, 5-44, 5-53 to 5-54, 5-58, 5-89 to 5-90

FindDialogItem function 6-125

FindDItem function. *See* FindDialogItem function

Finder

- application interface to 7-3 to 7-78
- database for a volume 7-45 to 7-46
- data structures used by 7-46 to 7-51
- defined 7-3 to 7-5

Finder (*continued*)

- and Process Manager 7-25
- relation to File Manager 7-3
- and Resource Manager 7-3

INDEX

resources used by 7-6 to 7-32, 7-56 to 7-70. *See also*
application-missing message string resources;
bundle resources; file reference resources; icon
list resources; large 8-bit color icon resources;
large 4-bit color icon resources; missing-
application name string resources; signature
resources; small 8-bit color icon resources; small
4-bit color icon resources; small icon list
resources; version resources

routines for 7-51 to 7-56

user interface guidelines for 7-13, 7-15

Finder flags 7-33 to 7-34, 7-47 to 7-48

Finder information, in the catalog file 7-32 to 7-34, 7-46
to 7-51

FindFolder function 7-54 to 7-56

FindWindow function 4-12, 4-44, 4-91 to 4-93, 5-32 to
5-33

and activate events 2-51

and mouse events 2-33 to 2-37, 4-42 to 4-44

FInfo data type 7-34, 7-47 to 7-49

“first click” in an inactive window 4-7, 4-42

'FKEY' resource type 2-39, 2-86, 3-118

FlashMenuBar procedure 3-141 to 3-142

'fld#' resource type 7-55

floppy disks, alias type for 7-40

'flpy' alias type 7-40

FlushEvents procedure 2-93 to 2-94

folder resources 7-55

folders

alias type for 7-40

finding system-related 7-53 to 7-56

folder types 7-54

'fold' file type 7-20

'FOND' resource type 3-69

'font' folder type 7-54

Font menu 3-26 to 3-27, 3-69 to 3-70

font resources

icon for 7-37 to 7-38

installing and removing 7-41

'FONT' resource type 3-69

fonts

bitmapped 3-27

suitcases for 7-37

TrueType 3-27

Fonts folder 7-44

foreground process 2-4

4-bit color icons 7-11

frames, window 4-6, 4-12 to 4-13

'FREF' resource type 7-18 to 7-25, 7-64 to 7-65

FrontWindow function 4-93 to 4-94

FSpGetFInfo function 7-34, 7-49

FSpSetFInfo function 7-34, 7-49

FXInfo data type 7-49

G

GetAlertStage function 6-66, 6-112

GetAlrtStage function. *See* GetAlertStage function

GetAuxCtl function. *See*
GetAuxiliaryControlRecord function

GetAuxiliaryControlRecord function 5-107

GetAuxWin function 4-115 to 4-116

GetCaretTime function 2-113

GetControlAction function 5-106

GetControlMaximum function 5-41 to 5-42, 5-61, 5-104

GetControlMinimum function 5-103 to 5-104

GetControlReference function 5-105

GetControlTitle procedure 5-104 to 5-105

GetControlValue function 5-38 to 5-39, 5-41 to 5-42,
5-44, 5-53 to 5-55, 5-61, 5-103

GetControlVariant function 5-106 to 5-107

GetCRefCon function. *See* GetControlReference
function

GetCTitle procedure. *See* GetControlTitle
procedure

GetCtlAction function. *See* GetControlAction
function

GetCtlMax function. *See* GetControlMaximum function

GetCtlMin function. *See* GetControlMinimum function

GetCtlValue function. *See* GetControlValue function

GetCVariant function. *See* GetControlVariant
function

GetCWMgrPort procedure 4-113 to 4-114

GetDblTime function 2-113

GetDialogItem procedure 6-50, 6-121 to 6-122

GetDialogItemText procedure 6-50, 6-130 to 6-131

GetDItem procedure. *See* GetDialogItem procedure

GetEvQHdr function 2-100

getFrontClicks flag 2-118

GetGray function 3-91

GetGrayRgn function 4-113

GetItemCmd procedure 3-138 to 3-139

GetItemImage procedure 3-137

GetItemMark procedure 3-135

GetItem procedure. *See* GetMenuItemText procedure

GetItemStyle procedure 3-133 to 3-134

GetIText procedure. *See* GetDialogItemText
procedure

GetKeys procedure 2-110

GetMBarHeight function 3-113

GetMCEntry function 3-145 to 3-146

GetMCInfo function 3-52, 3-143 to 3-144

GetMenuBar function 3-112

GetMenu function 3-55, 3-106 to 3-108

GetMenuHandle function 3-122

GetMenuItemText procedure 3-80, 3-132

GetMHandle function. *See* GetMenuHandle function

GetMouse procedure 2-108

INDEX

GetNewControl function 5-15 to 5-18, 5-24 to 5-25,
5-81 to 5-82
GetNewCWindow function 4-28, 4-76 to 4-77
GetNewDialog function 6-113 to 6-115
GetNewMBar function 3-50 to 3-52, 3-111 to 3-112
GetNewWindow function 4-28, 4-78 to 4-79
GetNextEvent function 2-21, 2-89 to 2-90
GetOSEvent function 2-97 to 2-98
GetPortNameFromProcessSerialNumber
function 2-107
GetProcessInformation function 2-74
GetProcessSerialNumberFromPortName
function 2-73, 2-82, 2-106
GetSpecificHighLevelEvent function 2-71, 2-77,
2-92 to 2-93
GetWindowPic function 4-110
GetWMgrPort procedure 4-114
GetWRefCon function 4-111
GetWTitle procedure 4-86
GetWVariant function 4-24, 4-112
global coordinates 4-17
GlobalToLocal procedure 5-34
graphics ports 4-17 to 4-18
gray areas, in scroll bars
action procedures for 5-58 to 5-61
defined 5-9
events in 5-57 to 5-61
part codes for 5-32
gray region 4-16
GrayRgn global variable 4-16, 4-95, 4-113, 4-116
grow images, of windows 4-57, 4-87
GrowWindow function 4-57 to 4-59, 4-99 to 4-100

H

hard disks, alias type for 7-40
hasBeenInited flag 7-48
hasBundle flag 7-34
hasCustomIcon flag 7-17 to 7-18, 7-34
hasNoINITS flag 7-48
'hdisk' alias type 7-40
help balloon resources 3-44, 3-68
help balloons
for icons 7-38
for window frames 4-23
help items, specifying in alert or dialog boxes 6-29 to
6-30, 6-155 to 6-156
Help menu 3-29 to 3-31
accessing from alert and dialog boxes 6-68 to 6-69
adding items to 3-67 to 3-68
handling 3-81
Hide Balloons command 6-68
Show Balloons command 6-68

Hide Balloons command (Help menu) 6-68
Hide Clipboard command (Edit menu) 3-25
HideControl procedure 5-39 to 5-40, 5-65 to 5-67, 5-97
HideDialogItem procedure 6-123 to 6-124
HideDItem procedure. *See* HideDialogItem procedure
Hide Others command (Application menu) 3-33
HideWindow procedure 4-61, 4-89
hierarchical menus 3-38, 3-53 to 3-56
high-level event message record 2-72, 2-82 to 2-83
HighLevelEventMsg data type 2-72, 2-82
high-level event queue 2-7, 2-13
high-level events 2-13 to 2-15, 2-67 to 2-78. *See also*
Apple events
accepting 2-69, 2-70
defined 2-13
determining the sender of 2-72
event classes 2-68
event IDs 2-68
handling 2-67 to 2-78
posting options 2-75
receiving 2-68, 2-87
replying to 2-74
and return receipts 2-77
searching for a specific event 2-71 to 2-72, 2-92
sending 2-73 to 2-77, 2-101
supporting 2-25
testing for availability 2-7
HiliteControl procedure 5-98 to 5-99, 6-13 to 6-14,
6-50 to 6-51, 6-74, 6-98
HiliteMenu procedure 3-71, 3-79, 3-119 to 3-120
HiliteWindow procedure 4-90
HiWord function 4-58
HMGetHelpMenuHandle function 3-67 to 3-68, 3-81,
3-123 to 3-124
'hmmu' resource type 3-44, 3-68
HMSetMenuResID procedure 6-71
hot spot 2-62
human interface guidelines. *See* user interface
guidelines

I, J

I-beam cursor 2-63
'icl8' resource type
creating 7-11, 7-24
Rez output format for 7-61 to 7-62
'icl4' resource type
creating 7-11, 7-24
Rez output format for 7-59 to 7-60
'ICN#' resource type
creating 7-11 to 7-15
example of 7-14 to 7-15
Rez output format for 7-57 to 7-58

INDEX

- specifying in a bundle resource 7-20
- icon families 7-11
- icon list resources
 - creating 7-11 to 7-15
 - example of 7-14 to 7-15
 - Rez output format for 7-57 to 7-58
 - specifying in bundle resources 7-20
- icon masks 7-13, 7-15
- icon resources ('ICON' resource type) 7-63
- 'ICON' resource type 7-63
 - specifying a menu item's 3-46, 3-62, 3-154
- icons. *See also* icon families
 - for applications 7-10 to 7-15
 - black and white 7-13, 7-15
 - color 7-15 to 7-16
 - creating 7-11 to 7-18
 - customizing 7-17 to 7-18
 - defaults used by Finder 7-12, 7-40
 - defined 7-3
 - for documents 7-16 to 7-18
 - for editions 7-16
 - 8-bit color 7-11
 - for font resources 7-37
 - 4-bit color 7-11
 - for keyboard layout resources 7-37
 - large 7-10, 7-13
 - for menu items 3-62 to 3-64
 - in menus 3-12, 3-62 to 3-64, 3-154
 - for query documents 7-16
 - reduced 3-62 to 3-63
 - for script system resource collections 7-37
 - small 7-13, 7-15
 - for sound resources 7-37
 - specifying in alert or dialog boxes 6-29 to 6-30, 6-154
 - for stationery pads 7-16, 7-19, 7-36
 - system 7-12
 - for TrueType font resources 7-37
- 'ics8' resource type
 - creating 7-11, 7-24
 - Rez output format for 7-62 to 7-63
- 'ics4' resource type
 - creating 7-11, 7-24
 - Rez output format for 7-60 to 7-61
- 'ics#' resource type
 - creating 7-11, 7-15, 7-24
 - Rez output format for 7-58 to 7-59
- 'ictb' resource type 6-158 to 6-164
- 'ifil' file type 7-37
- inactive controls 5-13, 6-13 to 6-14
- inactive windows 4-6 to 4-7
 - handling mouse-down events in 4-43
- indicators, in controls
 - defined 5-11
 - dragging 5-35, 5-99 to 5-100, 5-114 to 5-115
- Info box. *See* information windows
- information windows
 - using the stationery checkbox in 7-34
 - using to customize icon 7-17
 - version information in 7-8, 7-32
- InitDialogs procedure 6-103 to 6-104
- 'INIT' file type 7-44
- InitMenus procedure 3-103 to 3-104
- InitProcMenu procedure 3-104
- InitWindows procedure 4-75
- input methods 3-32
- InsertMenuItem procedure 3-64 to 3-67, 3-126 to 3-127
- InsertMenu procedure 3-55, 3-108 to 3-109
- InsertResMenu procedure 3-69, 3-129 to 3-130
- InsMenuItem procedure. *See* InsertMenuItem procedure
- InvalMenuBar procedure 3-114
- InvalRect procedure 4-107 to 4-108
- InvalRgn procedure 4-59, 4-108
- IPCListPorts function 2-74
- isAlias flag 7-40
- IsDialogEvent function 2-29, 6-77, 6-138 to 6-139
- isHighLevelEventAware flag 2-119
- isInvisible flag 7-34
- isOnDesk flag 7-48
- isShared flag 7-34, 7-48
- isStationeryAware flag 2-119
- isStationery flag 7-34
- is32BitCompatible flag 2-118
- item color table resources 6-158 to 6-164
- item list resources
 - counting items in 6-128
 - defined 6-13
 - example of 6-27 to 6-28
 - Rez input format for 6-26 to 6-30
 - Rez output format for 6-151 to 6-156
 - specifying for a dialog box 6-24
 - specifying for an alert box 6-20
- item numbers 6-28
- items in alert and dialog boxes. *See also* application-defined items; buttons; checkboxes; controls; editable text items; icons; item list resources; pictures; pop-up menus; radio buttons; static text items
 - adding 6-51 to 6-56, 6-125 to 6-127
 - copying editable text from 6-133
 - counting 6-128
 - creating 6-26 to 6-44
 - cutting editable text from 6-132 to 6-133
 - default colors of, changing 6-158 to 6-164
 - defined 6-13
 - deleting editable text from 6-134
 - display rectangles for 6-29, 6-32 to 6-35
 - drawing application-defined 6-143 to 6-144
 - enabled and disabled 6-13, 6-36
 - finding item numbers of 6-125

INDEX

- getting handles to 6-121 to 6-122
- getting text strings from 6-130 to 6-131
- hiding 6-123 to 6-124
- highlighting default text in 6-131 to 6-132
- item numbers for 6-28
- keyboard navigation 6-44
- manipulating 6-44 to 6-56, 6-120 to 6-128
- pasting editable text into 6-133 to 6-134
- pictures 6-29 to 6-30
- redisplaying after hiding 6-124
- removing 6-127 to 6-128
- setting or changing 6-122 to 6-123
- setting text strings in 6-131
- substituting text in 6-129 to 6-130
- types of 6-13 to 6-14, 6-30
- 'itlc' resource type 3-32, 3-33
- 'itlk' resource type 2-41

K

- 'KCHR' resource type 2-39 to 2-42, 3-17
- keyboard equivalents 3-18 to 3-19
 - commonly used 3-19
 - defining 3-47
 - reserved 3-18
- keyboard events
 - in alert boxes 6-86 to 6-89
 - in dialog boxes 6-79 to 6-80, 6-86 to 6-89, 6-94 to 6-97
 - handling 2-38 to 2-45
 - in windows 4-47
- keyboard layout resources 2-39 to 2-42, 3-17, 3-32, 3-33
- Keyboard menu 3-32 to 3-33
 - accessing from alert and dialog boxes 6-68 to 6-69
 - added by Menu Manager 3-19
- keyboard resources
 - icon for 7-37 to 7-38
 - 'KCHR' 2-39 to 2-42
 - 'KMAP' 2-21, 2-39 to 2-42
- keyboards 2-40
 - Apple Extended Keyboard II, domestic 2-43
 - Apple Extended Keyboard II, ISO 2-43
 - Apple Keyboard II, ISO 2-42
 - getting the state of 2-110
- key-down events
 - defined 2-8
 - handling keyboard equivalents 3-77 to 3-78
 - receiving 2-38 to 2-46
- KeyMap data type 2-110
- KeyTrans function. *See* KeyTranslate function
- KeyTranslate function 2-110 to 2-111, 3-78
- key-up events 2-8, 2-29
- 'kfil' file type 7-37
- KillControls procedure 5-108 to 5-109

- 'KMAP' resource type 2-21, 2-39 to 2-42

L

- Label menu commands 7-16
- large 8-bit color icon resources
 - creating 7-11, 7-24
 - Rez output format for 7-61 to 7-62
- large 4-bit color icon resources
 - creating 7-11, 7-24
 - Rez output format for 7-59 to 7-60
- large (32-by-32 pixel) icons 7-10, 7-11
- launching applications, from the Finder 7-25 to 7-26
- listings. *See* sample routines
- List Manager, and Control Manager 5-3
- localAndRemoteHLEvents flag 2-119
- local coordinates 4-18
- local IDs
 - in bundle resources and file reference resources 7-19, 7-22, 7-24
 - for mapping resources 7-18 to 7-25
- localization guidelines
 - for Control Manager 5-15, 5-19 to 5-20, 5-85, 5-120
 - for Dialog Manager 6-34 to 6-35, 6-39, 6-40, 6-80, 6-130
- location names 2-73, 2-75
- low-level events
 - handling 2-32 to 2-57
 - receiving 2-21
- LoWord function 4-58

M

- Macintosh Toolbox
 - features provided by 1-4
 - introduction to 1-3 to 1-16
- 'macs' folder type 7-54
- major switches 2-16
- marking character in a menu item 3-12
- masks
 - event. *See* event masks
 - icon 7-13, 7-15
- MBarEnable global variable 3-121
- 'MBAR' resource type 3-50, 3-155
- 'MBDF' resource type 3-9, 3-87, 3-104
- MCEnter data type 3-99
- MCTable data type 3-99
- MCTableHandle data type 3-99
- 'mctb' resource type 3-52, 3-99, 3-143, 3-155 to 3-157
- 'MDEF' resource type 3-87, 3-157
- memory, allocating 1-15

INDEX

- menu bars
 - accessing from alert and dialog boxes 6-68 to 6-73
 - creating 3-49 to 3-50
 - defined 3-6, 3-10
 - handling mouse-down events in 3-72
 - installing 3-41
- menu bar definition function 3-9, 3-87, 3-104
- MenuChoice function 3-118 to 3-119
- menu color information table 3-52, 3-98 to 3-102
 - menu bar entry 3-100
 - menu item entry 3-101
 - menu title entry 3-101
 - resources 3-155 to 3-157
- menu commands. *See also* menu items
 - About (Apple menu) 3-21
 - Can't Undo (Edit menu) 3-25
 - for changing colors in the Finder 7-16
 - Clear (Edit menu) 3-25, 6-68 to 6-69
 - Close (File menu) 3-23
 - Copy (Edit menu) 3-25, 6-68 to 6-69
 - Create Publisher (Edit menu) 3-25
 - Cut (Edit menu) 3-25, 6-68 to 6-69
 - Hide Balloons (Help menu) 6-68
 - Hide Clipboard (Edit menu) 3-25
 - Hide Others (Application menu) 3-33
 - keyboard equivalents for 3-16 to 3-19, 3-154
 - New (File menu) 3-23
 - None (Color menu) 7-16
 - Open (File menu) 3-23
 - Other (Size menu) 3-28
 - Page Setup (File menu) 3-23
 - Paste (Edit menu) 3-25, 6-68 to 6-69, 7-17
 - Print (File menu) 3-23
 - Publisher Options (Edit menu) 3-25
 - Quit (File menu) 3-23
 - Save (File menu) 3-23
 - Save As (File menu) 3-23
 - Select All (Edit menu) 3-25
 - Show Balloons (Help menu) 3-30, 6-68
 - Show Clipboard (Edit menu) 3-25
 - Subscriber Options (Edit menu) 3-25
 - Subscribe To (Edit menu) 3-25
 - Undo (Edit menu) 3-25, 6-68 to 6-69
- menu definition procedure 3-148 to 3-151
 - and the A5 register 3-150
 - defined 3-9
 - drawing color menus 3-91
 - handling scrolling in menus 3-91, 3-93
 - standard 3-148
 - writing 3-87 to 3-95
- menu handle 3-95, 3-122
- MenuHandle data type 3-95
- menu ID 3-40, 3-152
- MenuInfo data type 3-96 to 3-97
- menu items 3-12 to 3-16
 - in an accumulating group 3-15
 - adding to Apple menu 3-68 to 3-69
 - adding to Help menu 3-67 to 3-68
 - adding to menus 3-64 to 3-70
 - appearance of 3-12 to 3-14
 - changing
 - font style of 3-60
 - icon of 3-62 to 3-64
 - mark of 3-61 to 3-62
 - script code of 3-62
 - text of 3-59 to 3-60
 - characteristics of 3-12 to 3-14
 - disabling 3-8, 3-58 to 3-59, 3-74 to 3-77
 - divider 3-12
 - enabling 3-8, 3-58 to 3-59, 3-74 to 3-77
 - font style of 3-47, 3-154
 - grouping 3-14 to 3-16
 - handling user selection of 3-70 to 3-78
 - icon of 3-154
 - item numbers 3-40
 - keyboard equivalents for 3-16 to 3-19, 3-154
 - marking character of 3-154
 - metacharacters in 3-65
 - in a mutually exclusive group 3-14
 - providing help balloons for 3-7
 - script code of 3-47, 3-62, 3-154
 - script of 3-12
 - specifying the characteristics of 3-45 to 3-47
 - submenu for 3-47, 3-154
 - terms to use in help balloons and user
 - documentation 3-8
 - text of 3-12 to 3-13
- MenuKey function 3-71, 3-77 to 3-78, 3-117 to 3-118
- menu lists 3-40, 3-97 to 3-98
- Menu Manager 3-5 to 3-167
 - application-defined routines for 3-148 to 3-151
 - data structures in 3-95 to 3-102
 - data structures maintained by 3-40 to 3-41
 - and Dialog Manager 6-68 to 6-73
 - initializing 3-103 to 3-104
 - localization guidelines for 3-10, 3-16 to 3-18, 3-43
 - routine names, mapping of 3-102
 - routines in 3-102 to 3-147
 - testing for availability 3-42
 - user interface guidelines for 3-5 to 3-38
- menu records 3-40, 3-95 to 3-97
- menu resource 3-151 to 3-154
- 'MENU' resource type 3-42 to 3-48, 3-152 to 3-154
- menus. *See also* Apple menu; Application menu; Edit menu; File menu; Font menu; Help menu; Keyboard menu; Size menu; Style menu
 - accessing from alert and dialog boxes 3-84 to 3-86, 6-68 to 6-73
 - adding items to 3-64 to 3-70
 - adjusting items in 3-73 to 3-77

INDEX

- Apple. *See* Apple menu
 - Application. *See* Application menu
 - color 3-11
 - creating 3-42 to 3-57, 3-105 to 3-108
 - hierarchical 3-53 to 3-56
 - pop-up 3-56 to 3-57, 5-25 to 5-28, 6-42 to 6-44
 - pull-down 3-42 to 3-56
 - disabling for alert and dialog boxes 6-68 to 6-73
 - disposing of 3-112, 3-140
 - Edit. *See* Edit menu
 - File. *See* File menu
 - Font. *See* Font menu
 - grouping items in 3-14 to 3-16
 - Help. *See* Help menu
 - help balloons for 3-31
 - hierarchical 3-6, 3-38, 3-53 to 3-56
 - items in. *See* menu items
 - Keyboard. *See* Keyboard menu
 - keyboard equivalents for 3-16 to 3-19, 3-154
 - localizing 3-10
 - menu ID 3-152
 - pop-up. *See* pop-up menus
 - pull-down 3-6, 3-42
 - resource ID 3-44, 3-153
 - Size. *See* Size menu
 - Style. *See* Style menu
 - submenus 3-6, 3-53 to 3-56
 - system-handled 3-19
 - titles of 3-7, 3-10
 - types of 3-6
- MenuSelect function 3-8, 3-70, 3-72, 3-73, 3-78 to 3-79, 3-115 to 3-117
- message string resources 7-27 to 7-30
- minor switches 2-16
- missing-application name string resources 7-27 to 7-30, 7-68
- modal dialog boxes
 - accessing menus from 6-68 to 6-73
 - closing 6-100 to 6-101
 - creating 6-23 to 6-26, 6-113 to 6-119
 - defined 6-10 to 6-11
 - displaying 6-61, 6-62 to 6-75
 - event filter function for 6-86 to 6-89, 6-145 to 6-147
 - events in 6-82 to 6-86, 6-135 to 6-137
 - window types for 4-9
- ModalDialog procedure 6-84, 6-135 to 6-137
 - and disk-inserted events 2-56
 - and menus 3-86
- modeless dialog boxes
 - accessing menus from 6-68 to 6-73
 - closing 6-100 to 6-101
 - creating 6-23 to 6-26, 6-113 to 6-119
 - defined 6-12
 - displaying 6-61 to 6-67
 - events in 6-89 to 6-100, 6-138 to 6-141
 - titles for 6-25
 - window types for 4-10
- modifier keys 2-20 to 2-21, 2-81, 3-77
- mounted folder, alias type for 7-40
- mouse
 - determining location of 2-108
 - getting information about 2-108
- mouse-down events
 - in alert boxes 6-78, 6-81 to 6-82
 - in controls 5-11 to 5-13, 5-30 to 5-70
 - in desk accessories 2-87, 2-95
 - in dialog boxes 6-78 to 6-80, 6-82 to 6-94
 - handling 2-33 to 2-38
 - in the menu bar 3-72 to 3-73
 - in windows 4-42 to 4-45
- mouse driver 2-62
- mouse-moved events 2-23, 2-62 to 2-67, 2-86
- mouse region 2-23, 2-64 to 2-67
- mouse-up events 2-33
 - in alert boxes 6-78, 6-81 to 6-82
 - in controls 5-11 to 5-13, 5-30 to 5-70
 - in dialog boxes 6-78 to 6-80, 6-82 to 6-94
- movableDialogProc window type 3-85, 4-9, 6-25
- movable modal dialog boxes
 - accessing menus from 6-68 to 6-73
 - closing 6-100 to 6-101
 - creating 6-23 to 6-26, 6-113 to 6-119
 - defined 6-11 to 6-12
 - displaying 6-61, 6-62
 - events in 6-89 to 6-100, 6-138 to 6-141
 - titles for 6-25
 - window types for 4-9
- movable resources 7-36 to 7-38
- MoveControl procedure 5-67 to 5-70, 5-97 to 5-98
- MoveWindow procedure 4-95 to 4-96
- MultiFinder 2-7
- MyAction procedure 5-116 to 5-117
- MyAlertSound procedure 6-144 to 6-145
- MyControl function 5-110 to 5-115
- MyEventFilter function 6-145 to 6-147
- MyIndicatorAction procedure 5-117
- MyItem procedure 6-143 to 6-144

N

- nameLocked flag 7-18, 7-34
- name string resources for applications 7-27 to 7-30
- networks, using shared Trash directories on 7-44
- NewCDialog function. *See* NewColorDialog function
- NewColorDialog function 6-115 to 6-118
- New command (File menu) 3-23
- NewControl function 5-82 to 5-85
- NewCWindow function 4-79 to 4-82

INDEX

NewDialog function 6-118 to 6-119
NewMenu function 3-105 to 3-106
NewWindow function 4-82 to 4-85
noGrowDocProc window type 4-10, 6-25
NoteAlert function 6-110
note alerts
 creating with the NoteAlert function 6-110
 defined 6-8
Notification Manager, and operating-system
 events 2-12
null events
 defined 2-9
 and event masking 2-28
 handling 2-57

O

OldContent global variable 4-117
OldStructure global variable 4-117
onlyBackground flag 2-117
Open command (File menu) 3-23
OpenDeskAcc function 3-21, 3-80 to 3-81
Open Documents events 7-20, 7-25 to 7-26
opening
 applications, from the Finder 7-25 to 7-26
 disks 7-20
 documents 7-25 to 7-26
 folders 7-20
Operating System Event Manager 2-3, 2-7. *See also*
 Event Manager
Operating System event queue
 defined 2-6
 flushing events from 2-93
operating-system events
 defined 2-10 to 2-12
 handling 2-58 to 2-67
Option key 2-20
OSEventAvail function 2-98 to 2-99
Other command (Size menu) 3-28 to 3-29, 3-82 to 3-84

P

page regions, in scroll bars. *See* gray areas
Page Setup command (File menu) 3-23
PaintBehind procedure 4-118 to 4-119
PaintOne procedure 4-118
PaintWhite global variable 4-118, 4-119
Palette Manager, and system color tables 4-21
ParamText procedure 6-47, 6-129 to 6-130
part codes 5-31 to 5-32
partitions, sizes of 2-30, 2-115

Paste command (Edit menu)
 and dialog boxes 6-69
 and information windows 7-17
 introduced 3-25
PBGetCatInfo function 7-34, 7-49
PBMountVol function 2-55
pCDeskPat parameter-RAM bit flag 4-113
pictures, in alert or dialog boxes 6-29 to 6-30, 6-154
PinRect function 4-99
plainDBoxProc window type 4-9
pop-up menus 3-33 to 3-38
 action procedure for 5-36 to 5-37
 active 5-11 to 5-13
 control definition function for 3-33, 3-34 to 3-36, 5-14
 control definition ID for 5-14
 creating 3-56 to 3-57, 5-25 to 5-28
 defined 3-6, 5-6 to 5-7
 in dialog boxes 6-42 to 6-44
 events in, in windows 5-31 to 5-37
 inactive 5-11 to 5-13
 testing for availability 3-42
 type-in fields 3-37
 variation codes for 5-27 to 5-28
PopUpMenuSelect function 3-57, 3-120 to 3-121
popupPrivateData data type 5-77
port names 2-75
 converting to process serial numbers 2-105
 and receiving high-level events 2-73
port rectangle 4-18, 4-101, 4-103
 of Window Manager port 4-75
PostEvent function 2-104 to 2-105
PostHighLevelEvent function 2-73 to 2-77, 2-101 to
 2-103
posting options 2-75
PPCbrowser function
 filling in a target ID record 2-77
 finding a specific port 2-75
 posting a high-level event 2-74 to 2-75
PPC (Program-to-Program Communications)
 Toolbox 1-16, 2-7
PPostEvent function 2-103 to 2-104
preferences files 7-43
Preferences folder
 alias type for 7-40
 defined 7-43
 finding 7-54
 storing files in 7-43
'pref' folder type 7-54
Print command (File menu) 3-23
Print Documents events 7-25 to 7-26
PrintMonitor Documents folder
 alias type for 7-40
 defined 7-44
 finding 7-54
'prnt' folder type 7-54

INDEX

processes
 background 2-4
 context of 2-15
 foreground 2-4
 switching between 2-5, 2-15
Process Manager
 and Event Manager 2-3
 and the Finder 7-25
process serial numbers, converting to port
 names 2-105 to 2-107
Program-to-Program Communications (PPC)
 Toolbox 1-16, 2-7
Publisher Options command (Edit menu) 3-25
pull-down menus
 creating 3-43 to 3-52
 defined 3-6

Q

QHdr data type 2-83
query documents
 creating icons for 7-16, 7-17
 default icon for 7-12
 defined 7-4
QuickDraw 1-14. *See also* Color QuickDraw
 coordinate systems in 4-17 to 4-18
Quit command (File menu) 3-23

R

radio buttons
 active 5-11 to 5-13
 control definition ID for 5-14
 creating, in windows 5-20 to 5-21
 defined 5-6
 events in 6-78
 in windows 5-31 to 5-32
 inactive 5-11 to 5-13
 part code for 5-32
 specifying in alert or dialog boxes 6-153
rDocProc window type 4-10
rectangles, for controls 5-18 to 5-19, 5-25 to 5-26, 5-82,
 5-118. *See also* display rectangles
refCon field 4-111
reference values
 changing, for controls 5-105 to 5-106
 determining, for controls 5-105
 for pop-up menus 5-28
 specifying, for controls 5-18, 5-25, 5-84, 5-120
region codes, in version resources 7-31
requiresSwitchLaunch flag 7-48

Rescued Items from *volume name* folders 7-44
ResetAlertStage procedure 6-112
ResetAlrtStage procedure. *See* ResetAlertStage
 procedure
resizing windows 4-57 to 4-59
ResolveAliasFile function 7-52 to 7-53
resource forks 1-11
resource IDs
 for cursors 2-63
 defined 1-11
 for icons in menu items 3-62
Resource Manager 1-11 to 1-13
 and Control Manager 5-3
 and the Finder 7-3
resource maps 1-12
resources 1-11 to 1-13
 alert 6-19 to 6-22, 6-150 to 6-151
 alert color table 6-157 to 6-158
 alias record 7-40
 application-missing message string 7-68 to 7-69
 bundle 7-20 to 7-25, 7-65 to 7-68
 color icon 3-62, 7-64
 control 5-18 to 5-28, 5-118 to 5-121
 control color table 5-121 to 5-123
 control definition function 5-14, 5-109 to 5-115
 defined 1-11
 dialog 6-15, 6-24 to 6-26, 6-148 to 6-149
 dialog color table 6-75 to 6-76, 6-156 to 6-157
 driver 3-20, 3-68, 3-129, 3-130
 file reference 7-18 to 7-25, 7-64 to 7-65
 folder 7-55
 font 3-69
resources (*continued*)
 font family 3-69
 icon 3-62, 7-63
 icon list 7-13, 7-57 to 7-58
 international configuration 3-32
 item color table 6-158 to 6-164
 item list. *See* item list resources
 keyboard-layout 2-39
 key-map 2-39, 2-41, 2-42
 key-remap 2-39, 2-41
 large 8-bit color icon 7-61 to 7-62
 large 4-bit color icon 7-59 to 7-60
 menu 3-151 to 3-154
 menu bar 3-155
 menu bar definition function 3-9, 3-87, 3-104
 menu color information table 3-155 to 3-157
 menu definition procedure 3-157
 missing-application name string 7-68
 movable 7-36 to 7-38
 signature 7-8 to 7-10
 size 2-115 to 2-119, 7-35
 small 8-bit color icon 7-62 to 7-63
 small 4-bit color icon 7-60 to 7-61

INDEX

small icon 3-62
small icon list 7-58 to 7-59
sound 7-37 to 7-38
string 3-60
string list 3-60, 3-65 to 3-67
System file, in the 1-12
used by the Finder 7-6 to 7-32
version 7-31 to 7-32, 7-69 to 7-70
window 4-22, 4-25 to 4-27, 4-124 to 4-127
window color table 4-127 to 4-129
window definition function 4-22, 4-120, 4-127

resource types 1-11

- 'actb' 6-157 to 6-158
- 'alis' 7-40
- 'ALRT'. *See* alert resources
- 'BNDL' 7-20 to 7-25, 7-65 to 7-68
- 'cctb' 5-121 to 5-123
- 'CDEF' 5-14, 5-109 to 5-115
- 'cicn' 3-62, 3-154, 7-64
- 'CNTL' 5-18 to 5-28, 5-118 to 5-121
- 'dctb' 6-156 to 6-157
- 'DITL'. *See* item list resources
- 'DLOG'. *See* dialog resources
- 'DRVR' 3-20, 3-68, 3-129, 3-130
- 'FKEY' 2-39, 3-118
- 'fld#' 7-55
- 'FOND' 3-69, 3-129, 3-130
- 'FONT' 3-69, 3-129, 3-130
- 'FREF' 7-18 to 7-25, 7-64 to 7-65
- 'hmmu' 3-44, 3-68
- 'icl8' 7-61 to 7-62
- 'icl4' 7-59 to 7-60
- 'ICN#' 7-20, 7-57 to 7-58
- 'ICON' 3-62, 3-154, 7-63
- 'ics8' 7-62 to 7-63
- 'ics4' 7-60 to 7-61
- 'ics#' 7-15, 7-58 to 7-59
- 'ictb' 6-158 to 6-164
- 'itlc' 3-32
- 'itlk' 2-41
- 'KCHR' 2-39 to 2-42
- 'KMAP' 2-39 to 2-42
- 'MBAR' 3-155
- 'MBDF' 3-9, 3-87, 3-104
- 'mctb' 3-155 to 3-157
- 'MDEF' 3-157
- 'MENU' 3-151 to 3-154
- 'SICN' 3-62, 3-154
- 'SIZE' 2-115 to 2-119, 7-35
- 'STR' 3-60, 7-27 to 7-30
- 'STR#' 3-60, 3-65 to 3-67
- 'vers' 7-31 to 7-32, 7-69 to 7-70
- 'wctb' 4-127 to 4-129
- 'WDEF' 4-22, 4-120, 4-127
- 'WIND' 4-22, 4-25 to 4-27, 4-124 to 4-127

resume events
 defined 2-10
 handling 2-60 to 2-62
ResumeProc global variable 6-172
return receipts 2-75, 2-77
RGBColor data type 5-79

S

sample code. *See* sample routines

sample routines

- DisplayMyDialog 6-58
- DoActivate 2-53, 4-51 to 4-52
- DoActivateGlobalChangesDialog 6-98
- DoCloseCmd 4-60 to 4-61, 6-94
- DoContentClick 5-33, 5-53, 6-92
- DoCopyResource 7-29
- DoDiskEvent 2-56
- DoDrumRollCheckBox 5-38
- DoEvent 2-26, 3-72, 3-77
- DoGlobalChangesDialog 6-67
- DoGraphicsScroll 5-47
- DoGrowWindow 4-58 to 4-59
- DoHighLevelEvent 2-70
- DoIdle 2-57, 6-79
- DoKeyDown 2-44, 3-78, 6-95
- DoMenuCommand 3-79
- DoMouseDown 2-34, 3-72, 4-44 to 4-45, 5-32, 6-91
- DoNew 5-24
- DoNewCmd 4-28 to 4-29

sample routines (*continued*)

- DoOpenFile 4-37 to 4-38
- DoOSEvent 2-59
- DoPlayButton 5-36
- DoPopUpMenu 5-37
- DoSaveAsCmd 7-28
- DoShowModelessFindDialogBox 4-64
- DoSpellBoxWithSpanish 6-54
- DoSuspendResumeEvent 2-61
- DoUpdate 2-50, 4-50, 5-29, 5-62, 6-99
- DoZoomWindow 4-55 to 4-56
- IsStationeryDoc 7-36
- MyAddHelpItem 3-68
- MyAdjustCursor 2-65
- MyAdjustEditMenuForDocWindow 3-75
- MyAdjustEditMenuForModalDialogs 6-72
- MyAdjustFileMenuForDocWindow 3-74
- MyAdjustHV 5-41
- MyAdjustMenus 3-73, 6-70
- MyAdjustMenusForDialogs 6-70
- MyAdjustScrollBars 5-39
- MyAdjustScrollSizes 5-67
- MyAdjustScrollValues 5-40

INDEX

- MyAlert 6-66
- MyAlertSound 6-22
- MyChangeMenuBarAndSaveColorInfo 3-52
- MyCloseDocument 4-61 to 4-62, 6-47
- MyCreatePlaySoundsWindow 5-17
- MyDrawDefaultButtonOutline 6-59
- MyDrawGraphicsWindow 5-63
- MyDrawWindow 4-39, 5-30, 5-65
- MyEventFilter 6-88
- MyEventLoop 2-24
- MyGetLocalUpdateRgn 4-60
- MyGetWindowType 4-24
- MyHandleAppleCommand 3-80
- MyHandleHelpCommand 3-81
- MyHandleKeyDown 2-44, 6-95
- MyHandleKeyDownInModeless 6-96
- MyHandleModelessDialogs 6-49
- MyHandleSizeCommand 3-83
- MyHorzntlActionProc 5-59
- MyMakeAllMenus 3-70
- MyMakeMenus 3-50
- MyMakeSubMenu 3-55
- MyMDEF 3-89
- MyMoveScrollBar 5-61
- MyOpen 7-41
- MyPostTest 2-74
- MyPostWithPPCBrowser 2-76
- MyResizeWindow 4-59
- MySaveWindowPosition 4-34 to 4-35
- MySetWindowPosition 4-36 to 4-37
- MySpellCheckDialog 6-83
- MyToggleHideShow 3-59
- MyVerticalActionProc 5-59
- ShowMyAboutBox 6-65
- UserDidCancel 2-46
- Save As command (File menu) 3-23
- Save command (File menu) 3-23
- SaveOld procedure 4-117
- SaveUpdate global variable 4-118
- SaveVisRgn global variable 4-106
- scrap
 - converting global to private 2-12
 - converting private to global 2-12
- scrap coercion 2-58, 2-61
- Scrap Manager 1-14, 2-60
- 'scri' file type 7-44
- script, changing a menu item's 3-62, 3-154
- script code, for menu item text 3-47, 3-62
- script system resource collections, icon for 7-37
- scroll arrows
 - action procedures for 5-58 to 5-61
 - defined 5-8 to 5-9
 - events in 5-57 to 5-61
 - part codes for 5-32
- scroll bars. *See also* gray areas; scroll arrows; scroll boxes
 - activating 5-13
 - active 5-11 to 5-13
 - changing settings and display of 5-9 to 5-10, 5-39 to 5-43, 5-44, 5-61, 5-70
 - control definition ID for 5-14
 - creating, in windows 5-21 to 5-25
 - defined 5-7 to 5-10
 - document scrolling with 5-9 to 5-10, 5-43 to 5-70
 - events in 5-31 to 5-32, 5-43 to 5-65
 - inactive 5-11 to 5-13
 - and List Manager 5-3
 - moving and resizing 5-65 to 5-70
 - updating 5-30
 - as a window element 4-6
- scroll boxes
 - action procedure for 5-36
 - defined 5-7 to 5-8
 - dragging 5-35
 - events in 5-53 to 5-57
 - moving 5-9 to 5-10, 5-39 to 5-43, 5-44, 5-61, 5-70
 - part code for 5-32
- ScrollRect procedure 5-46 to 5-48, 5-56 to 5-57
- Select All command (Edit menu) 3-25
- SelectDialogItemText procedure 6-131 to 6-132
- SelectWindow procedure 2-51, 4-87 to 4-88
- SelectItemText procedure. *See* SelectDialogItemText procedure
- SendBehind procedure 4-91
- servers, alias type for 7-40
- session reference number 2-73
- SetControlAction procedure 5-102
- SetControlColor procedure 5-101
- SetControlMaximum procedure 5-41 to 5-43, 5-70, 5-95 to 5-96
- SetControlMinimum procedure 5-95
- SetControlReference procedure 5-105 to 5-106
- SetControlTitle procedure 5-96
- SetControlValue procedure 5-38 to 5-39, 5-42 to 5-43, 5-44, 5-61, 5-94 to 5-95
- SetCRefCon procedure. *See* SetControlReference procedure
- SetTitle procedure. *See* SetControlTitle procedure
- SetCtlAction procedure. *See* SetControlAction procedure
- SetCtlColor procedure. *See* SetControlColor procedure
- SetCtlMax procedure. *See* SetControlMaximum procedure
- SetCtlMin procedure. *See* SetControlMinimum procedure
- SetDAFont procedure. *See* SetDialogFont procedure
- SetDeskCPat procedure 4-112 to 4-113
- SetDialogFont procedure 6-105
- SetDialogItem procedure 6-122 to 6-123

INDEX

- SetDialogItemText procedure 6-131
- SetDItem procedure. *See* SetDialogItem procedure
- SetEventMask procedure 2-99 to 2-100
- SetItemCmd procedure 3-139 to 3-140
- SetItemImage procedure 3-62 to 3-64, 3-137 to 3-138
- SetItemMark procedure 3-61 to 3-62, 3-135 to 3-136
- SetItem procedure. *See* SetMenuItemText procedure
- SetItemStyle procedure 3-60, 3-134
- SetIText procedure. *See* SetDialogItemText procedure
- SetMCEntries procedure 3-146 to 3-147
- SetMCInfo procedure 3-52, 3-144
- SetMenuBar procedure 3-50 to 3-51, 3-112 to 3-113
- SetMenuFlash procedure 3-142
- SetMenuItemText procedure 3-59 to 3-60, 3-133
- SetOrigin procedure 5-44 to 5-45, 5-63 to 5-64
- SetPort procedure 6-62
- SetWinColor procedure 4-114 to 4-115
- SetWindowPic procedure 4-110
- SetWRefCon procedure 4-111
- SetWTitle procedure 4-85
- 'sfil' file type 7-37
- shared folder, alias type for 7-40
- Shift key 2-20
- ShortenDITL procedure 6-127 to 6-128
- Show Balloons command (Help menu) 6-68
- Show Clipboard command (Edit menu) 3-25
- ShowControl procedure 5-39 to 5-40, 5-66 to 5-67, 5-86
- ShowDialogItem procedure 6-124
- ShowDItem procedure. *See* ShowDialogItem procedure
- ShowHide procedure 4-89 to 4-90
- ShowWindow procedure 4-88, 6-61
- 'SICN' resource type, specifying a menu item's 3-62, 3-154
- signature resources 7-8 to 7-10
- signatures
 - in bundle resources 7-20
 - as creators 7-9
 - defined 7-8
 - registering 7-8 to 7-10
- 16-by-16 pixel (small) icons 7-11, 7-15
- size box 4-6
- SizeControl procedure 5-67 to 5-70, 5-98
- Size menu 3-27 to 3-29, 3-82
 - handling 3-82 to 3-84
 - Other command in 3-28 to 3-29
- size region 4-12
- size resources 2-115 to 2-119, 7-35
- 'SIZE' resource type 2-115 to 2-119, 7-35
 - creating 2-30 to 2-32
 - defined 2-30 to 2-32, 2-115 to 2-119
 - flags, defined 2-116 to 2-119
 - and null events 2-9, 2-57
 - sample Rez input 2-31
 - scheduling option flags 2-16
 - setting flags for high-level events 2-68
 - setting flags of 2-9, 2-11, 2-16, 2-51
- SizeWindow procedure 4-60, 4-101
- sleep value 2-22
- slider controls 5-11
- small 8-bit color icon resources
 - creating 7-11, 7-24
 - Rez output format for 7-62 to 7-63
- small 4-bit color icon resources
 - creating 7-11, 7-24
 - Rez output format for 7-60 to 7-61
- small icon list resources
 - creating 7-11, 7-15, 7-24
 - Rez output format for 7-58 to 7-59
- small (16-by-16 pixel) icons
 - resource IDs for 7-15
 - resources for 7-10
- sound resources
 - icon for 7-37 to 7-38
 - installing and removing 7-41
- 'srvr' alias type 7-40
- stack, size of 2-32
- standard control definition function 5-14
- standard file dialog boxes, and disk-inserted events 2-55
- Standard File Package, and disk-inserted events 2-55 to 2-56
- standard state of a window 4-33, 4-53, 4-70
- Startup Items folder
 - alias type for 7-40
 - defined 7-44
 - finding 7-54
- static text items
 - getting text from 6-130 to 6-131
 - setting text in 6-36 to 6-41, 6-131, 6-153
 - specifying in alert or dialog boxes 6-29 to 6-30, 6-153
 - substituting text in 6-46 to 6-48
 - substituting text strings in 6-129 to 6-130
 - user interface guidelines for 6-40 to 6-41
- stationery pads
 - creating icons for 7-16, 7-19
 - default icon for 7-12
 - defined 7-4, 7-34 to 7-36
 - recognition of 2-119
- StillDown function 2-109
- StopAlert function 6-109
- stop alerts
 - creating with the StopAlert function 6-109
 - defined 6-9
- 'STR ' resource type 3-60, 7-27 to 7-30
- 'STR#' resource type 3-60, 3-65 to 3-67
- 'strt' folder type 7-54
- structure region 4-6, 4-12
- Style data type 3-134
- StyleItem data type 3-134

INDEX

Style menu 3-15
 example of 3-15
 and the Font menu 3-27
 keyboard equivalents for 3-19
styles
 changing a menu item's 3-47, 3-60
 of a menu item 3-12
submenus
 creating 3-53 to 3-56
 defined 3-6
Subscriber Options command (Edit menu) 3-25
Subscribe To command (Edit menu) 3-25
suitcases for fonts and desk accessories 7-37
suspend events
 defined 2-10
 handling 2-60 to 2-62
switching
 context 2-15
 major 2-16
 minor 2-16
system alert sounds 6-8, 6-22
SystemClick procedure 2-87, 2-94 to 2-95, 4-43, 4-44
system color tables, and Palette Manager 4-21
SystemEdit function 3-122
SystemEvent function 2-96
system event masks 2-28 to 2-29, 2-99
system extensions
 and Extensions folder 7-44
 installing and removing 7-41
System file 7-44
System Folder
 alias type for 7-40
 defined 7-5
 finding 7-54
 organization of 7-41 to 7-45
system-handled menus 3-19
SystemMenu procedure 3-121
SystemTask procedure 2-25, 2-87, 2-95 to 2-96

T

TargetID data type 2-72, 2-81
target ID records 2-81 to 2-82
 receiving 2-73
 sending 2-75
'temp' folder type 7-54
temporary files 7-43, 7-44
Temporary Items folder
 defined 7-43
 finding 7-54
TEPinScroll procedure 5-55 to 5-56
TestControl function 5-93
TEUpdate procedure 5-64 to 5-65

text
 in buttons, checkboxes, and radio buttons 5-18, 5-19,
 5-19 to 5-20, 5-25, 6-37 to 6-40, 6-153
 editable, in dialog boxes. *See* editable text items
 handling 1-14 to 1-15
 static, in alert and dialog boxes. *See* static text items
TextEdit
 and Dialog Manager 6-79 to 6-80
 handling text 1-14 to 1-15
 and mouse events 2-37
'TEXT' file type 7-10
text style table 6-160, 6-162 to 6-164
32-by-32 pixel (large) icons 7-11, 7-13
thumb controls. *See* scroll boxes
TickCount function 2-112
Ticks global variable 2-112
title bar 4-5
titles
 of buttons, checkboxes, and radio buttons 6-37 to
 6-40, 6-153
 changing, for controls 5-96
 determining, for controls 5-104 to 5-105
 for modeless and movable modal dialog boxes 6-25
 specifying for controls 5-18, 5-19 to 5-20, 5-25, 5-83,
 5-85, 5-120, 5-121
Toolbox Event Manager. *See* Event Manager
TopMenuItem global variable 3-151
TrackBox function 4-44, 4-101 to 4-102
TrackControl function 5-35 to 5-37, 5-44, 5-53 to 5-55,
 5-58, 5-90 to 5-92, 6-78
 and pop-up menus 3-56
TrackGoAway function 4-44, 4-103 to 4-104
Trash, alias type for 7-40
Trash directories
 appearance to users 7-42
 defined 7-44
 finding 7-54
'trsh' alias type 7-40
'trsh' folder type 7-54
TrueType fonts 7-37. *See also* fonts

U

Undo command (Edit menu) 3-25, 6-69
UpdateControls procedure 5-86 to 5-87
UpdateDialog procedure 6-142 to 6-143
update events 4-13
 in alert boxes 6-82, 6-86 to 6-89
 defined 2-9
 in dialog boxes 6-85, 6-86 to 6-89, 6-97 to 6-100
 handling 2-47 to 2-50, 4-48 to 4-50
 routines for handling 4-106 to 4-107
 for windows 4-41

INDEX

update region
 defined 4-13
 maintaining 4-41
 redrawing 4-40 to 4-41
UpdtControl procedure. *See* UpdateControls
 procedure
UpdtDialog procedure. *See* UpdateDialog procedure
user interface guidelines
 for Control Manager 5-52 to 5-53
 for controls 5-5 to 5-13
 for Dialog Manager 6-8 to 6-12, 6-31 to 6-34, 6-37 to
 6-41, 6-42, 6-62 to 6-64
 for icons 7-13, 7-15
 for static text items 6-40 to 6-41
 for windows 4-5 to 4-7, 4-21, 4-30 to 4-32
user-oriented design 1-5
user state of a window 4-33, 4-53, 4-70
useTextEditServices flag 2-119

V

ValidRect procedure 4-58, 4-108 to 4-109
ValidRgn procedure 4-109
variation codes
 for controls, defined 5-14
 determining, for controls 5-106 to 5-107
 for windows 4-11, 4-112, 4-120
version information for applications
 in Finder windows 7-31
 in information windows 7-32
 in signature resource 7-8
 in 'vers' resource 7-31 to 7-32
version resources 7-31 to 7-32, 7-69 to 7-70
'vers' resource type 7-31 to 7-32, 7-69 to 7-70
virtual key codes 2-40
 of Apple Extended Keyboard II, domestic 2-43
 of Apple Extended Keyboard II, ISO 2-43
 of Apple Keyboard II, ISO 2-42
visible region 4-48
volume catalogs, Finder information in 7-32 to 7-34
volumes, Finder's desktop database for 7-45

W, X, Y

WaitMouseUp function 2-109
WaitNextEvent function 2-85 to 2-88
 introduced 2-22 to 2-24
 and multitasking 2-60
'wctb' resource type 4-71, 4-127 to 4-129
'WDEF' resource type 4-22, 4-120, 4-127
WinCTab data type 4-71 to 4-72

window color table 4-21, 4-71 to 4-73
window definition functions
 defined 4-10
 writing 4-120 to 4-124
window definition IDs
 creating windows, used in 4-80, 4-83 to 4-84
 defined 4-11
 for a dialog box 6-25
 and window definition functions 4-120
 in window resources 4-26, 4-125
window frames 4-6, 4-12 to 4-13, 4-121 to 4-122
window list 4-15, 4-74
WindowList global variable 4-74
Window Manager 4-3 to 4-129
 application-defined routine for 4-120 to 4-124
 and Control Manager 4-14 to 4-15, 5-3
 data structures in 4-65 to 4-74
 and Dialog Manager 4-13 to 4-14, 6-15 to 6-16
Window Manager (*continued*)
 events generated by 2-9
 global variables 4-75
 port 4-74
 resources in 4-124 to 4-129
 routines in 4-74 to 4-119
 initializing 4-74 to 4-75
 low-level routines 4-116 to 4-119
window origin
 changing 5-44 to 5-45, 5-48 to 5-52
 defined 5-45
WindowPeek data type 4-20, 4-65
window positioning constants 4-32
WindowPtr data type 4-19, 4-65
WindowRecord data type 4-19, 4-65, 4-69
window records 4-19 to 4-20, 4-65 to 4-69
window regions 4-12 to 4-13
window resources 4-22, 4-25 to 4-27, 4-124 to 4-127
windows 4-3 to 4-129
 activating 4-50 to 4-53
 active 4-6
 alert boxes and dialog boxes
 deactivating behind 6-64 to 6-66
 as types of 6-15 to 6-17
 closing 4-60 to 4-62, 4-103 to 4-106
 color in 4-20 to 4-21, 4-71 to 4-74
 content region 4-12
 controls in 4-14 to 4-15, 5-82
 creating 4-25 to 4-30, 4-75 to 4-85
 deallocating 4-61 to 4-62, 4-104 to 4-106
 defined 4-4
 displaying 4-86 to 4-91
 drawing content region 4-39 to 4-40
 events in 4-21, 4-22, 4-41 to 4-53
 grow image 4-57, 4-87
 hiding 4-62 to 4-64, 4-89
 inactive 4-6 to 4-7

INDEX

- maintaining update region of 4-106 to 4-109
- managing multiple 4-15 to 4-16, 4-23 to 4-25
- manipulating
 - characteristics 4-109 to 4-112
 - color 4-114 to 4-116
 - on the desktop 4-112 to 4-114
- mouse-down events in 4-42 to 4-45
- moving 4-53, 4-94 to 4-99
- naming 4-85 to 4-86
- parts drawn by the Window Manager 4-12 to 4-13
- positioning 4-30 to 4-38
- regions in 4-12 to 4-13
- resizing 4-57 to 4-59
- responding to activate events in 2-50 to 2-55, 4-50 to 4-53
- retrieving information 4-91 to 4-94
- scrolling 5-9 to 5-10, 5-43 to 5-70
- showing 4-62 to 4-64, 4-88
- sizing 4-99 to 4-101
- standard state 4-33, 4-53, 4-70
- structure region 4-12
- types of 4-8 to 4-10
- updating 2-47 to 2-50, 4-40 to 4-41, 4-48 to 4-50, 5-49 to 5-52, 5-62 to 5-65
- user state 4-33, 4-53, 4-70
- window-manipulation conventions 4-21
- window resources, defining 4-25 to 4-27
- zooming 4-53 to 4-56, 4-101 to 4-103
- window state data record 4-33, 4-54, 4-70 to 4-71
- window types 4-8 to 4-11
- 'WIND' resource type 4-22, 4-25 to 4-27, 4-124 to 4-127
- wristwatch cursor 2-63
- WStateData data type 4-33, 4-54, 4-70 to 4-71

Z

- zoom box 4-6
- zoomDocProc window type 4-8
- zooming windows 4-53 to 4-56, 4-101 to 4-103
- zoomNoGrow window type 4-10
- zoom region 4-12
- ZoomWindow procedure 4-54, 4-57, 4-102 to 4-103

This Apple manual was written, edited, and composed on a desktop publishing system using Apple Macintosh computers and FrameMaker software. Proof pages were created on an Apple LaserWriter IINTX printer. Final page negatives were output directly from text files on an AGFA ProSet 9800 imagesetter. Line art was created using Adobe™ Illustrator. PostScript™, the page-description language for the LaserWriter, was developed by Adobe Systems Incorporated.

Text type is Palatino® and display type is Helvetica®. Bullets are ITC Zapf Dingbats®. Some elements, such as program listings, are set in Apple Courier.

LEAD WRITER

Sharon Everson

WRITERS

Sharon Everson, Tony Francis,
Sue Luttner

DEVELOPMENTAL EDITORS

Sue Factor, Antonio Padial, Anne Szabla,
Beverly Zegarski

INDEX SPECIALIST

Sanborn Hodgkins

ILLUSTRATORS

Bruce Lee, Ruth Anderson,
Pat Rogondino, Martine Trelaun

COVER DESIGNER

Barb Smyth

PRODUCTION EDITOR

Rex Wolf

PROJECT MANAGER

Patricia Eastman

Special thanks to Ray Chiang,
Kevin MacDonell, Dave Radcliffe,
Jim Reekes

Acknowledgments to Eric Anderson,
Randy Carr, John Glenn, Sandee Karr,
Peggy Kunz, Tim Monroe, Dave Owens,
Dean Yu, and the entire *Inside Macintosh*
team.